

Title (en)

METHOD FOR DETERMINING SWITCHGEAR-RELATED DATA IN SWITCHGEAR CONTACTS AND/OR OPERATION-RELATED DATA IN A CONNECTED NETWORK

Title (de)

VERFAHREN ZUR BESTIMMUNG VON SCHALTGERÄTESPEZIFISCHEN DATEN AN KONTAKTEN IN SCHALTGERÄTEN UND/ODER VON BETRIEBSPEZIFISCHEN DATEN IM DAMIT GESCHALTEHEN NETZ

Title (fr)

PROCEDE POUR DETERMINER DES DONNEES SPECIFIQUES D'APPAREILS DE COMMUTATION AU NIVEAU DE CONTACTS INSTALLEES DANS LESDITS APPAREILS DE COMMUTATION ET/OU DONNEES SPECIFIQUES DE FONCTIONNEMENT DANS UN RESEAU COMMUTE DE FAÇON CORRESPONDANTE

Publication

EP 1002325 B1 20020320 (DE)

Application

EP 98948727 A 19980805

Priority

- DE 9802247 W 19980805
- DE 19734224 A 19970807

Abstract (en)

[origin: DE19734224C1] The invention relates to a method in which the contact spring action at the break is detected, in particular for earthing contacts, as a replacement criterion for the erosion of contacts. Erosion can be determined by measuring the change in contact spring action during the switching off process, and converted to give the residual life of the contacts. This requires precise measurement of the armature path from the beginning of the armature movement to the beginning of the contact opening. In accordance with the invention, the switching conditions in the switchgear and in the electric network can also be detected from the signals used for determining the contact spring action.

IPC 1-7

H01H 1/00

IPC 8 full level

H01H 1/00 (2006.01)

CPC (source: EP US)

H01H 1/0015 (2013.01 - EP US)

Cited by

DE10260248A1; DE10260248B4; DE10260249A1; DE10260249B4; DE10260258A1; DE10260258B4; US7812696B2

Designated contracting state (EPC)

DE FR IT

DOCDB simple family (publication)

DE 19734224 C1 19990204; CN 1138288 C 20040211; CN 1267392 A 20000920; DE 59803443 D1 20020425; EP 1002325 A1 20000524; EP 1002325 B1 20020320; US 6313636 B1 20011106; WO 9908301 A1 19990218

DOCDB simple family (application)

DE 19734224 A 19970807; CN 98808208 A 19980805; DE 59803443 T 19980805; DE 9802247 W 19980805; EP 98948727 A 19980805; US 49985400 A 20000207