

Title (en)
Yarn suction device and yarn suction and cut device

Title (de)
Fadenabsaugvorrichtung und Fadenabsaug- und Fadenschneidvorrichtung

Title (fr)
Dispositif d'aspiration de fil et dispositif d'aspiration et de coupe de fil

Publication
EP 1004534 A3 20001206 (EN)

Application
EP 99123526 A 19991125

Priority
• JP 33531798 A 19981126
• JP 1121099 A 19990119

Abstract (en)
[origin: EP1004534A2] The present invention provides a yarn sucking and cutting device in a yarn winding machine for traversing and winding a yarn that enables a yarn to be reliably sucked. A yarn suction device 13 comprises a suction port 14 of a yarn suction path 15 that is open so as to face a yarn traverse plane P for a yarn Y, and a yarn guide member 16 for advancing and withdrawing between a standby position E at which it does not intersect the traverse plane P and guide position F at which it intersects the traverse plane. The yarn guide member 16 comprises yarn guide surfaces 16c, 16c that each assume a position for leading the yarn from the traverse plane P to the vicinity of the suction port 14 when the yarn guide member 16 has advanced to the guide position 16. The yarn guide member 16 comprises a cover section 16a for closing the suction port 14 once the yarn guide member 16 has withdrawn to the standby position E. A common compresses air path 22 comprising an opening and closing valve 24 is connected to both an operation member 19 for moving the yarn guide member 16 forward using the force of supplied compressed air and a yarn suction path 15 for effecting suction through the suction port 14 using supplied compressed air. <IMAGE>

IPC 1-7
B65H 54/88; **B65H 54/71**; **B65H 67/04**

IPC 8 full level
B65H 35/00 (2006.01); **B65H 54/71** (2006.01); **B65H 54/88** (2006.01); **B65H 67/04** (2006.01)

CPC (source: EP KR)
B65H 35/00 (2013.01 - KR); **B65H 54/71** (2013.01 - EP); **B65H 54/88** (2013.01 - EP); **B65H 67/04** (2013.01 - EP); **B65H 2701/31** (2013.01 - EP)

Citation (search report)
• [XA] EP 0156306 A1 19851002 - BARMAG BARMER MASCHF [DE]
• [X] US 4165046 A 19790821 - SUZUKI YOSHIHISA, et al
• [X] US 5284010 A 19940208 - DAMMANN PETER [DE]
• [XDA] US 5423170 A 19950613 - DAMMANN PETER [DE], et al
• [A] EP 0659673 A1 19950628 - MENEGATTO SRL [IT]
• [PXA] WO 9957051 A1 19991111 - BARMAG BARMER MASCHF [DE], et al
• [X] PATENT ABSTRACTS OF JAPAN vol. 1996, no. 09 30 September 1996 (1996-09-30)

Cited by
CN112141814A; EP1447367A1; CN1314572C

Designated contracting state (EPC)
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
EP 1004534 A2 20000531; **EP 1004534 A3 20001206**; KR 100471102 B1 20050307; KR 20000052386 A 20000825

DOCDB simple family (application)
EP 99123526 A 19991125; KR 19990053172 A 19991126