

Title (en)

Method and device for plastically forming a hollow cylinder with internal gear teeth

Title (de)

Verfahren und Vorrichtung zur plastischen Formgebung eines Hohlzylinders mit Innenverzahnung

Title (fr)

Procédé et dispositif pour la formation plastique d'un cylindre creux à denture intérieure

Publication

**EP 1005932 A3 20010829 (DE)**

Application

**EP 99106390 A 19990327**

Priority

DE 19852261 A 19981113

Abstract (en)

[origin: EP1005932A2] Hollow cylinder with inner teeth is plastically formed by a device incorporating a press matrix and press die. The press matrix comprises a counter bearing (4) and ring-shaped cover (3) for accommodating a cylindrical blank (8) with central hole. The press die has a cylindrical pin (1b) and tooth-cutting tool (1a). The diameter of the pin corresponds to the inner diameter of the blank with a slight under-dimension. The tooth-cutting tool on its outer periphery is provided with the profile (6) of the desired inner teeth of the hollow cylinder. The counter bearing (4) has a cavity (7) for accommodation of the pin when the tooth cutting tool is moved completely inwards.

IPC 1-7

**B21J 5/12; B21K 1/30**

IPC 8 full level

**B21J 5/12** (2006.01); **B21K 1/30** (2006.01)

CPC (source: EP US)

**B21J 5/12** (2013.01 - EP US); **B21K 1/30** (2013.01 - EP)

Citation (search report)

- [X] US 5325698 A 19940705 - NAGPAL VIJAY [US], et al
- [A] US 4452060 A 19840605 - KANAMARU HISANOBU [JP], et al
- [AD] EP 0322770 A2 19890705 - MH CENTER LTD [JP], et al
- [AD] EP 0356118 A2 19900228 - FORD MOTOR CO [GB], et al
- [A] PATENT ABSTRACTS OF JAPAN vol. 1995, no. 04 31 May 1995 (1995-05-31)

Cited by

CN108421838A; CN102896268A; CN114273571A; US7168281B2; WO03080271A1; DE102011122144A1; DE102011122144B4

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

**EP 1005932 A2 20000607; EP 1005932 A3 20010829**

DOCDB simple family (application)

**EP 99106390 A 19990327**