

Title (en)

Microcontroller controlled electric steam generator without separate sensors

Title (de)

Mikroprozessor gesteuerter elektrischer Dampferzeuger ohne separate Sensoren

Title (fr)

Générateur de vapeur électrique commandé par un micro-processeur sans capteurs séparés

Publication

**EP 1010937 A1 20000621 (EN)**

Application

**EP 99204312 A 19991215**

Priority

NL 1010813 A 19981215

Abstract (en)

An apparatus with which, by means of electric energy, steam can be generated. The invention makes use of the positive temperature coefficient of the heating resistance of the heating element. Through the use of a microcontroller in the electronics, the current through and the voltage across the heating element can continuously be determined and hence be used for determining and controlling the steam humidity and the pressure of the steam. For this, in principle, no other, separate sensors are needed anymore. Due to the small mass of the through-flow heater, the electronic control can respond rapidly to fluctuations. In view of a predictable through-flow, a spiral-shaped labyrinth is provided. During operation, water flows through the labyrinth. In the first part, the temperature rises from starting temperature to boiling temperature. After that, the temperature of the water up to the outlet of the through-flow heater can be at boiling temperature. Said temperature variation determines the resistance of the heating element. The steam humidity can be adjusted through the system by controlling the pump power. When the flow rate is increased, the steam humidity rises, which is measured by the drop of the resistance of the heating element and can be controlled thereby. Depending on the type of steam generator, an electronically settable excess-pressure valve can be provided on the outlet of the through-flow heater. Upon blocking of the steam outlet, the current supply to the heating element is interrupted. The boiling dry of the through-flow heater leads to direct switching off as well. The electronics are self-testing and switch off the through-flow heater if an error occurs. <IMAGE>

IPC 1-7

**F22B 1/28**

IPC 8 full level

**F22B 1/28** (2006.01)

CPC (source: EP)

**F22B 1/288** (2013.01)

Citation (search report)

- [A] DE 19509772 C1 19960711 - DRAEGERWERK AG [DE]
- [A] EP 0595292 A1 19940504 - PLANETA HAUSGERAETE [DE]
- [A] EP 0333916 A2 19890927 - HERAEUS WITTMANN GMBH [DE]
- [A] DE 3232169 A1 19840301 - LICENTIA GMBH [DE]
- [A] PATENT ABSTRACTS OF JAPAN vol. 098, no. 005 30 April 1998 (1998-04-30)

Cited by

CN114263953A; EP1516632A1; US7476369B2; US7801424B2; EP1484961B2; EP1815737B1

Designated contracting state (EPC)

DE FR GB IT NL

DOCDB simple family (publication)

**EP 1010937 A1 20000621; EP 1010937 B1 20030903**; DE 69910960 D1 20031009; NL 1010813 C2 20000619

DOCDB simple family (application)

**EP 99204312 A 19991215**; DE 69910960 T 19991215; NL 1010813 A 19981215