

Title (en)  
REDUNDANCY SYSTEM WITH "1:N" AND "1:1" REDUNDANCY FOR A ASN-SYSTEM

Title (de)  
REDUNDANZSYSTEM MIT "1:N" UND "1:1" REDUNDANZ FÜR EIN ASN-SYSTEM

Title (fr)  
SYSTEME DE REDONDANCE "1:N" ET "1:1" POUR SYSTEME ASN

Publication  
**EP 1016238 A1 20000705 (DE)**

Application  
**EP 98955333 A 19980915**

Priority  
• DE 9802734 W 19980915  
• DE 19740741 A 19970916

Abstract (en)  
[origin: WO9914886A1] The communication facility (KE) described presents a coupling configuration (ASN) of at least a number N of active power electronics assemblies (BG 1 to BG N), each being connected to at least one transmission line (LTG 1 to LTG N) and forming with an additional standby power electronic assembly (BG N+1) a redundancy group "1:N". In such a facility, the power electronic assemblies are arranged in pairs on the same model as a "1:1" redundancy. The power electronic assemblies in said facility have switching means (S1, S2) owing to which, when a defect occurs in one of said groups, an alternative path is defined which passes through the corresponding partner-power electronics assembly and the standby power electronic assembly.

IPC 1-7  
**H04L 1/22**; **H04L 12/56**

IPC 8 full level  
**H04L 1/22** (2006.01); **H04L 49/111** (2022.01)

CPC (source: EP)  
**H04L 1/22** (2013.01); **H04L 49/105** (2013.01); **H04L 49/3081** (2013.01); **H04L 49/552** (2013.01); **H04L 2012/5627** (2013.01)

Citation (search report)  
See references of WO 9914886A1

Designated contracting state (EPC)  
BE CH DE ES FR GB IT LI NL

DOCDB simple family (publication)  
**WO 9914886 A1 19990325**; AU 1223299 A 19990405; AU 739406 B2 20011011; CA 2303538 A1 19990325; CN 1270723 A 20001018; EP 1016238 A1 20000705; ZA 988380 B 19990316

DOCDB simple family (application)  
**DE 9802734 W 19980915**; AU 1223299 A 19980915; CA 2303538 A 19980915; CN 98809192 A 19980915; EP 98955333 A 19980915; ZA 988380 A 19980914