

Title (en)
Method for sound deadening a piece of sheet metal

Title (de)
Verfahren zum Entdröhnen eines Blechteiles

Title (fr)
Procédé pour amortir le son d'une pièce en tôle

Publication
EP 1018725 A3 20010808 (DE)

Application
EP 00100002 A 20000103

Priority
DE 19900106 A 19990105

Abstract (en)
[origin: EP1018725A2] A method for preventing drumming in sheet metal parts (A) involves fixing metal plate(s) (B) to the part (A) by means of screws, rivets or welded joints plus an adhesive layer consisting of an acrylate ester copolymer for usage temperatures of -20 to +50 degrees C or a crosslinked silicone adhesive for use at 0-100 degrees C.

IPC 1-7
G10K 11/168; F02B 77/11

IPC 8 full level
G10K 11/168 (2006.01)

CPC (source: EP)
G10K 11/168 (2013.01)

Citation (search report)

- [X] US 4707397 A 19871117 - MORIMURA YASUHIRO [JP], et al
- [A] US 3386527 A 19680604 - DAUBERT GEORGE A, et al
- [A] US 4681816 A 19870721 - HASHIMOTO MIKIO [JP], et al
- [Y] GB 2113346 A 19830803 - BEKAERT SA NV
- [Y] DE 9204724 U1 19920611
- [Y] DE 1182862 B 19641203 - GRUENZWEIG & HARTMANN
- [A] DE 3408411 A1 19850919 - RUETGERSWERKE AG [DE]
- [A] DE 19739778 A1 19980312 - TOKAI RUBBER IND LTD [JP]
- [A] US 3087571 A 19630430 - KERWIN JR EDWARD M
- [A] US 3640836 A 19720208 - OBERST HERMANN, et al
- [DA] DE 9104672 U1 19910627
- [A] DE 1147768 B 19630425 - BECCHIS OSIRIDE S A S

Cited by
CN107405868A; DE10061457A1; DE102004020631A1; DE102004020631B4; US2017011730A1; US9978353B2; WO2018149719A1; WO2016131629A1; WO2005104322A1; WO2018149720A1; WO2018149717A1

Designated contracting state (EPC)
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
EP 1018725 A2 20000712; EP 1018725 A3 20010808

DOCDB simple family (application)
EP 00100002 A 20000103