

Title (en)

Method for adjusting the torque for force transmission of a magnetic drive agitator

Title (de)

Verfahren zur Drehmomenteinstellung für die Kraftübertragung eines Rührwerk mit magnetischem Antrieb

Title (fr)

Procédé du réglage du couple limite de transmission d'effort d'un agitateur à entraînement magnétique

Publication

EP 1023936 B2 20070307 (FR)

Application

EP 99420233 A 19991126

Priority

FR 9901130 A 19990128

Abstract (en)

[origin: EP1023936A1] The rotor can be moved in translation parallel to the X-X' axis inside the sleeve between a first position where the two means of coupling are matching to drive the helix in rotation and a second position where they do not interact or interact little, so the helix can be displaced relative to the sleeve without the two couplings interacting. The agitator comprises a union (5) which can be mounted in a sealed fashion in a wall (2a) of a receiver with a blind sleeve (10) inside which is fitted a rotor (20) supporting a first magnetic coupling (21). A helix (8) placed around the sleeve is equipped with a second magnetic coupling (17) to drive the helix around an axis (X-X') of rotation. The rotor can be moved in rotation around and parallel to the axis X-X' by a drive shaft (22) which is itself movable in rotation around and parallel to the X-X' axis between two positions corresponding to those of the rotor. The rotor has a central hollow to receive a screw for mounting the rotor on the shaft, with the screw placed along the X-X' axis. The rotor and/or shaft can be immobilized during their parallel movement in an intermediate position. The drive shaft is mounted to slide inside a hollow shaft which is the output from a reduction gear, with the two shafts fixed together in rotation. The hollow shaft has a screw which acts with a fillet fixed to the drive shaft. The parallel movement is controlled by a hydraulic or pneumatic jack. Process of controlling couple transmitted to a magnetic agitator as described above by controlling the position of the rotor along the X-X' axis.

IPC 8 full level

B01F 13/08 (2006.01)

CPC (source: EP US)

B01F 33/453 (2022.01 - US); **B01F 33/4535** (2022.01 - EP)

Cited by

CN110098537A; FR2854663A1; EP1475566A3

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

EP 1023936 A1 20000802; **EP 1023936 B1 20030108**; **EP 1023936 B2 20070307**; AT E230628 T1 20030115; CA 2291500 A1 20000728; CA 2291500 C 20080527; DE 69904803 D1 20030213; FR 2788995 A1 20000804; FR 2788995 B1 20010406; US 6206562 B1 20010327

DOCDB simple family (application)

EP 99420233 A 19991126; AT 99420233 T 19991126; CA 2291500 A 19991202; DE 69904803 T 19991126; FR 9901130 A 19990128; US 45910399 A 19991213