

Title (en)

Device and system for positioning a weft yarn in a gripper loom

Title (de)

Vorrichtung und Anordnung zum Vorlegen eines Schussfadens für eine Greiferwebmaschine

Title (fr)

Dispositif et système pour positionner un fil de trame dans un métier à tisser à griffes

Publication

**EP 1024214 A1 20000802 (DE)**

Application

**EP 99811211 A 19991224**

Priority

- EP 99811211 A 19991224
- EP 99810074 A 19990128

Abstract (en)

The assembly to lay the weft yarns at a gripper loom has a linear motor with a stator (4) containing two permanent magnets (7), and an armature (5) with a coil (22). The weft yarn laying finger (2) is connected to the linear motor to present the weft at the gripper. The linear motor and the yarn laying finger (2) form a modular component group. The magnet holder (6) has a V-shaped cross section, with an opening (13) or holder to take the permanent magnets (7). The magnet holder (6) is of iron or a plastics material. The sliding units (9) for the armature (5) are in the holder (6). The linear motor has a core (21) of plastics, and two frame side sections (23) of a non-magnetic material to cover the coil (22). The sides are separated by a gap to reduce the eddy current effect. The linear motor can have a coil carrier with two legs, with a gap between the ends of the legs to reduce the eddy current effect. An Independent claim is included for a weft laying system at the gripper loom, with a number of units arranged in a fan shape at a holder structure, so that they can be exchanged separately. Preferred Features: The armature (5) of one linear motor is passed into the adjacent linear motor.

Abstract (de)

Die Vorrichtung enthält einen Linearmotor (1) mit einem Stator (4), der zwei Permanentmagnete (7) aufweist und mit einem Anker (5), der eine Wicklung (22) aufweist und ein Fadenvorlegefinger '(2) für den Schussfaden, das mit dem Linearmotors verbunden ist, um den Schussfaden einem Greifer vorzulegen. Der Linearmotor (1) und der Fadenvorlegefinger (2) ist als modulare Baugruppe ausgebildet. <IMAGE>

IPC 1-7

**D03D 47/38**

IPC 8 full level

**D03D 47/38** (2006.01)

CPC (source: EP)

**D03D 47/38** (2013.01)

Citation (search report)

- [Y] EP 0598264 A1 19940525 - PICANOL NV [BE]
- [YD] EP 0347626 A2 19891227 - SCAVINO MARIO
- [PX] EP 0894883 A2 19990203 - NUOVO PIGNONE SPA [IT]
- [A] EP 0461524 A1 19911218 - VAMATEX SPA [IT]
- [A] PATENT ABSTRACTS OF JAPAN vol. 98, no. 2 30 January 1998 (1998-01-30)

Cited by

CN101935909A; CN104005159A; EP3926649A1; IT202000014749A1

Designated contracting state (EPC)

BE DE IT

DOCDB simple family (publication)

**EP 1024214 A1 20000802; EP 1024214 B1 20060517**

DOCDB simple family (application)

**EP 99811211 A 19991224**