

Title (en)
Method and device for stufferbox crimping a yarn

Title (de)
Verfahren und Vorrichtung zum Stauchkräuseln eines Fadens

Title (fr)
Procédé et dispositif pour le frisage à boîte de bourrage d'un fil

Publication
EP 1026295 A3 20031126 (DE)

Application
EP 00100230 A 20000117

Priority
DE 19904973 A 19990206

Abstract (en)
[origin: EP1026295A2] For crimping a multifilament yarn, it is compressed into a plug, and its temp. is lowered in a cooling channel. The free end of the yarn is pulled free from the plug at the end of the cooling stage and the release point for the yarn at the plug is controlled by the yarn take-off speed. On a change of the yarn take-off speed, a signal is passed to the control with at least one parameter affecting the formation of the yarn plug. The yarn take-off speed change reverts to given time points through a comparison between the nominal (V_{soll}) and actual (V_{ist}) speeds. A signal is generated when $V_{soll} \leq V_{ist}$ and $V_{soll} \geq V_{ist}$, and no signal is produced when $V_{soll} = V_{ist}$. In the event where $V_{soll} \leq V_{ist}$, the signal triggers a parameter change to reduce the packing density of the yarn plug, and vice versa. The take-off speed is returned to a given nominal value at set time points and, at the same time, the release point of the yarn at the plug is registered so that the signal is triggered on a change in the yarn release position. If the yarn plug is shortened, the signal trips a parameter change to reduce the plug packing density, and vice versa. The parameter of the crimping appts. is formed by the heating temp. and/or the advance movement pressure, which are adjustable to form the yarn plug. The yarn take-off speed and/or the crimping appts. parameter are adjustable within given threshold limits, and the yarn plug formation is interrupted if the take-off speed and crimping appts. parameters are breached. The yarn take-off speed is modified by the action of a winder where it is wound on a bobbin. Or the take-off speed is set by a take-off unit which extracts the yarn from the plug at a constant tension for winding on a bobbin. An independent claim is included for a yarn crimping appts. with a control (20) which determines at least the parameter for the crimping appts. (2) which affects the formation of the yarn plug (3). The crimping appts. control (20) has a signal link (19) to the take-off control (17). The appts. can have a texturizing jet with an expansion chamber to form the yarn plug (3). The temp. and/or the plug advance pressure of the advance movement system is the parameter which is varied by the control (20). The take-off control (17) has a timer to control the position of the yarn release point at the plug (3) by reversion time points in a time sequence. The control (20) is linked to a sensor (18). The yarn take-off is a winder (13) where the yarn is wound on a bobbin, and its control (17) is connected to the winder drive. The take-off also has a rotating godet roller (10), between the cooling stage (4) and the bobbin winder (13), and the yarn (1) is wound on a bobbin (14) at a constant tension.

IPC 1-7
D02G 1/12; **G01N 33/36**

IPC 8 full level
D02G 1/12 (2006.01)

CPC (source: EP US)
D02G 1/122 (2013.01 - EP US); **D02G 1/125** (2013.01 - EP US); **D02G 1/161** (2013.01 - EP US); **D02G 1/167** (2013.01 - EP US)

Citation (search report)

- [DA] DE 4224454 A1 19930204 - BARMAG BARMER MASCHF [DE]
- [A] US 3961401 A 19760608 - FERRIER DUNCAN CAMERON, et al
- [A] GB 946553 A 19640115 - BARMAG BARMER MASCHF
- [A] US 5802832 A 19980908 - FOSTER PETER WILLIAM [GB]
- [A] US 5351374 A 19941004 - NABULON WERNER [CH], et al
- [A] US 4337557 A 19820706 - MCDONALD WILLIAM J, et al

Cited by
EP1607500A1; DE102004029219A1; WO2006076933A1

Designated contracting state (EPC)
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
EP 1026295 A2 20000809; **EP 1026295 A3 20031126**; US 6305059 B1 20011023

DOCDB simple family (application)
EP 00100230 A 20000117; US 49609900 A 20000201