

Title (en)  
Hydrostatic pump

Title (de)  
Hydrostatische Pumpe

Title (fr)  
Pompe hydrostatique

Publication  
**EP 1026401 A3 20010926 (DE)**

Application  
**EP 00101946 A 20000201**

Priority  
DE 19904339 A 19990203

Abstract (en)  
[origin: EP1026401A2] The side plate(16) of the pump is loaded by a disc spring(30) in the direction of the displacement chamber, and the pump casing(2) is sealed on the end face side. The displacement component is a vane wheel. A rotor(6) is torsionally fixed on the shaft(4) and supports radially movable vanes(8), the end sections of which lie closely upon the inner circumference of a thrust ring(10) mounted in the pump casing. The side plate is preloaded against the thrust ring and cell wheel by the disc spring.

IPC 1-7  
**F04C 2/344; F04C 15/00**

IPC 8 full level  
**F04C 2/344** (2006.01); **F04C 15/00** (2006.01)

CPC (source: EP)  
**F01C 21/108** (2013.01); **F04C 2/3442** (2013.01); **F04C 15/0023** (2013.01)

Citation (search report)  
• [X] FR 1121395 A 19560813  
• [X] US 3362339 A 19680109 - ECKFELDT EDGAR L, et al  
• [X] DE 9201060 U1 19920319  
• [X] US 3549288 A 19701222 - NICHOLS DENVER E, et al  
• [X] DE 19631846 A1 19970220 - LUK FAHRZEUG HYDRAULIK [DE]

Cited by  
EP3081741A3; CN107178496A; US10458406B2; WO2009135587A3; US10082139B2; US11143181B2; EP3081741B1

Designated contracting state (EPC)  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)  
**EP 1026401 A2 20000809; EP 1026401 A3 20010926; EP 1026401 B1 20030611**; DE 19904339 A1 20000810; DE 50002506 D1 20030717

DOCDB simple family (application)  
**EP 00101946 A 20000201**; DE 19904339 A 19990203; DE 50002506 T 20000201