

Title (en)

Device and method for disassembling connection pins

Title (de)

Einrichtung und Verfahren zum Lösen von Verbindungsbolzen

Title (fr)

Dispositif et procédé pour dégager des axes de jonction

Publication

**EP 1027960 A3 20030709 (DE)**

Application

**EP 00102838 A 20000211**

Priority

DE 19906126 A 19990213

Abstract (en)

[origin: EP1027960A2] The tool consists of two horizontal jointed levers with facing inner end faces (11,21) and a pressure tool between the faces. The inner end face (21) of a first lever (2) has a pressure part (8), which I placed on the head of a connection bolt (18). The inner end face (11) of the second lever (1) has a cylindrical recess, which is placed on an expander bolt (23). A extraction unit (24) extends through the recess and is connected to the end of the connection bolt.

IPC 1-7

**B25B 27/02; B25B 27/04**

IPC 8 full level

**B25B 27/02** (2006.01); **B25B 27/04** (2006.01); **B25B 31/00** (2006.01)

CPC (source: EP US)

**B25B 27/026** (2013.01 - EP US); **B25B 27/04** (2013.01 - EP US); **B25B 31/00** (2013.01 - EP US); **Y10T 29/53896** (2015.01 - EP US)

Citation (search report)

- [A] US 5031311 A 19910716 - COMENSOLI JEAN-CLAUDE [FR]
- [A] GB 626146 A 19490711 - GIUSEPPE CRISTINA
- [AD] DE 4434152 A1 19950601 - KLANN HORST [DE]
- [A] US 5850679 A 19981222 - HOFFMAN JAY F [US]
- [A] US 5210919 A 19930518 - GARMAN JAMES A [US]

Cited by

CN108817898A; DE102006013069B3; CN113119022A

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

**EP 1027960 A2 20000816; EP 1027960 A3 20030709; EP 1027960 B1 20060607**; DE 19906126 A1 20000831; DE 19906126 C2 20001130;  
DE 50012873 D1 20060720; ES 2264655 T3 20070116; US 6336264 B1 20020108

DOCDB simple family (application)

**EP 00102838 A 20000211**; DE 19906126 A 19990213; DE 50012873 T 20000211; ES 00102838 T 20000211; US 50354800 A 20000214