

Title (en)
Cable covered with a heat shrinkable web

Title (de)
Kabel mit einer wärmeschrumpfbaaren Materialbahnumhüllung

Title (fr)
Câbles enveloppes d'une bande en matériau thermorétractable

Publication
EP 1033443 A1 20000906 (FR)

Application
EP 00400527 A 20000228

Priority
• FR 9902504 A 19990301
• FR 9912783 A 19991013

Abstract (en)
The shrouding (2) for at least one band of cables or strands is a strip of heat shrinking material which is applied to lock the cables. The sealed joints have collars (5) round the cables for the circulation of dry air within the shrouding, along the length of the cables. The strip has two lips projecting from the outer surfaces of the two edges so that, when they are brought together at their flat surfaces, they form a beading at right angles to the contact surfaces. A slide is pushed over the beading to lock the edges together during heat shrinking, which can be removed after shrinking or left in place as a mechanical reinforcement of the joint. A system gives a dry air circulation between the shrouding (2) and the cables, in the gaps formed after shrinkage. The shrouding is formed by a number of strips (2) wrapped round the cables, overlapping each other. The shrouding also covers the metal collars, as a seal between them. The collar sections (6,7) are locked together by a screw bolt clamp (8). The seal can also be a neck within the collar around the heat shrinking shrouding material. A cord of sealing putty is around the ring collar and the shrouding as the seal, or a shaped unit is molded or fitted on the collar by a clamp where one shrouding strip is between the sealing piece and the cables and another shrouding strip is outside the sealing piece and round the first shrouding strip. The heat shrinking strip is locked to the metal collar without cladding, with a string of sealing putty as the bond between the strip and the end of the collar. The edges of the shrouding strip can have projecting lips at one side, to form a beading when they are brought together, to be locked by a slide pushed over them. One lip is set back from the edge, by 20-70 mm and preferably 40 mm, as a space for an applied thermofusible adhesive which is compressed during shrinkage. The beadings, formed by the lips, have a semi-circular cross section. An Independent claim is included for a cable shrouding process where the shrouding material is cut to length and laid along the cables, and is wrapped round them to bring their edges together with the edge lips projecting outwards forming a beading, to be locked together by a slide pushed over them. The shrouding is heated to shrink the material, and to bond the edges together by the fusible adhesive between them. The slide can be removed and the lips trimmed off flush to the shrouding, or the slide can be left in place to reinforce the bond at the shrouding edges. Preferred Features: The zone of bumps formed by the lips and the slide is covered by a putty to give a support zone in a regular convex shape with a width of 6 cm and a length of 20-40 cm, where the first shrouding strip is partially covered by the second strip together with an additional bonding strip to hold the edges together during shrinkage. The second strip covers the first longitudinally to enclose the end of the lip and slide bumps for complete sealing.

Abstract (fr)
Ouvrage, notamment un pont, comportant au moins un faisceau de câbles (1) ou fils et des moyens (2, 2', 2'') de protection de la périphérie extérieure des câbles, les moyens (2, 2', 2'') de protection sont constitués d'une bande, en un matériau thermorétractable, disposée d'une manière à envelopper par ajustement serré le faisceau de câbles (1) ou fils et à réaliser des jonctions étanches avec les colliers disposés sur le faisceau de façon à pouvoir faire circuler de l'air sec à l'intérieur de l'enveloppe ainsi formée sur toute la longueur du faisceau, la bande (2, 2', 2'') comportant deux lèvres (35, 38) issues de la face extérieure des deux bords (31, 32) de la bande, les deux lèvres (35, 38) étant adjacentes par une face (36) de contact et comportant chacune un bourrelet (37) s'étendant sensiblement perpendiculairement à ladite face (36) de contact, de manière à pouvoir enfiler une glissière (39) de maintien commune sur les lèvres (35, 38) adjacentes pour les maintenir l'une contre l'autre pendant la thermorétraction et ensuite la retirer ou la laisser en place pour renforcer mécaniquement la liaison. <IMAGE> <IMAGE>

IPC 1-7
E01D 19/16; D07B 1/16

IPC 8 full level
D07B 1/16 (2006.01); **E01D 19/16** (2006.01)

CPC (source: EP)
D07B 1/162 (2013.01); **E01D 19/16** (2013.01); **D07B 2201/2089** (2013.01); **D07B 2205/2089** (2013.01); **D07B 2207/404** (2013.01)

Citation (search report)
• [XAY] EP 0722015 A1 19960717 - D S BROWN COMPANY INC [US]
• [YA] DE 3730376 C1 19890223 - KINZINGER WILLY
• [XA] WO 9211997 A1 19920723 - RAYCHEM SA NV [BE]
• [A] EP 0350822 A2 19900117 - BILFINGER BERGER VORSPANNTTECH [DE]
• [A] US 4718965 A 19880112 - FINSTERWALDER ULRICH [DE], et al
• [A] GB 839138 A 19600629 - GEN ELECTRIC

Cited by
CN103848323A

Designated contracting state (EPC)
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
EP 1033443 A1 20000906; FR 2790493 A1 20000908; FR 2790493 B1 20010914; NO 20001019 D0 20000229; NO 20001019 L 20000904

DOCDB simple family (application)
EP 00400527 A 20000228; FR 9912783 A 19991013; NO 20001019 A 20000229