

Title (en)
Switch with security welding

Title (de)
Schalter mit Verschweissicherung

Title (fr)
Interrupteur a soudage de sécurité

Publication
EP 1033732 A3 20020619 (DE)

Application
EP 99124508 A 19991209

Priority
DE 19909059 A 19990302

Abstract (en)
[origin: EP1033732A2] The switch has a fixed contact pad (26) that is engaged by a movable contact (25) on the tip of a bimetallic element (23). Bimetallic element is coupled to a leaf spring (17). Contact between pad (26) and contact (25) is opened if too high ambient temperature or due to current flow. At the end of its operational life, arcing which occurs as contact opens welds movable contact in the open position.

IPC 1-7
H01H 1/50; H01H 37/54

IPC 8 full level
H01H 1/50 (2006.01); **H01H 37/54** (2006.01); **H01H 3/00** (2006.01)

CPC (source: EP US)
H01H 1/50 (2013.01 - EP US); **H01H 37/54** (2013.01 - EP US); **H01H 3/001** (2013.01 - EP US); **H01H 2001/506** (2013.01 - EP US);
H01H 2037/5463 (2013.01 - EP US)

Citation (search report)
• [X] EP 0828273 A2 19980311 - HOFSAESS MARCEL PETER [DE]
• [XP] EP 0938116 A2 19990825 - HOFSAESS MARCEL [DE]
• [A] US 4399423 A 19830816 - NIELD JOSEPH G [US]
• [A] PATENT ABSTRACTS OF JAPAN vol. 1995, no. 11 26 December 1995 (1995-12-26)

Designated contracting state (EPC)
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
EP 1033732 A2 20000906; EP 1033732 A3 20020619; EP 1033732 B1 20040609; AT E268937 T1 20040615; DE 19909059 A1 20000921;
DE 19909059 C2 20031016; DE 59909688 D1 20040715; ES 2221294 T3 20041216; PT 1033732 E 20041029; US 6448883 B1 20020910

DOCDB simple family (application)
EP 99124508 A 19991209; AT 99124508 T 19991209; DE 19909059 A 19990302; DE 59909688 T 19991209; ES 99124508 T 19991209;
PT 99124508 T 19991209; US 51639200 A 20000301