

Title (en)
Rotary variable resistor and output regulator using the same

Title (de)
Drehwiderstand und diesen verwendendes Steuerungssystem

Title (fr)
Résistance variable par rotation et système de contrôle l'utilisant

Publication
EP 1035551 A2 20000913 (EN)

Application
EP 00105001 A 20000309

Priority
JP 6447699 A 19990311

Abstract (en)
A rotary variable resistor comprising a resistive film (33) formed on an insulating substrate (302), a current collecting conductive member (36) disposed in such a manner as to be concentric with the resistive film (33) and to be spatially isolated from the resistive film (33) and the lead members (34) thereof (33), a circular arc shaped auxiliary conductive member (39) formed in such a manner as to be concentric with the resistive film (33), and to be spatially isolated from the resistive film (33), the current collecting conductive member (36) and the lead members (34,37) of the patterns (33,36), also to cover a larger angular range than the angular opening of the resistive film (33), a first brush (31) made of an elastic metal plate and fixed to an operation shaft which is repeatedly rotatable, also having first contact portions (42) which respectively elastically contact to the resistive film (33) and to the current collecting conductive member (36), wherein the first brush (31) forms a first resistor unit (43) together with the resistive film (33) and the current collecting conductive member (36), and, a second brush (32) made of an elastic metal plate and fixed to the operation shaft in such a manner as to be electrically isolated from the first brush (31), also having second contact portions (44) which respectively elastically contact to the resistive film (33) and to the auxiliary conductive member (39) in the rotational angular range of the operation shaft, in which a predetermined output voltage is unobtainable from the first resistor unit (43), wherein the second brush (32) forms a second resistor unit (45) together with the resistor film (33) and the auxiliary conductive member (39). The above structure simplifies the pattern structure of a resistor board (30) and decreases the number of terminals, also simplify the production process. <IMAGE>

IPC 1-7
H01C 10/32

IPC 8 full level
H01C 10/00 (2006.01); **H01C 10/32** (2006.01); **H01C 10/34** (2006.01)

CPC (source: EP)
H01C 10/34 (2013.01)

Cited by
FR2913272A1; WO2008107279A1

Designated contracting state (EPC)
DE FR GB IT

DOCDB simple family (publication)
EP 1035551 A2 20000913; **EP 1035551 A3 20040107**; **EP 1035551 B1 20050706**; DE 60021130 D1 20050811; DE 60021130 T2 20060420; JP 2000260607 A 20000922

DOCDB simple family (application)
EP 00105001 A 20000309; DE 60021130 T 20000309; JP 6447699 A 19990311