

Title (en)
Latch on a press tool

Title (de)
Verschluss an einem Presswerkzeug

Title (fr)
Loquet sur un outil de sertissage

Publication
EP 1036608 B1 20030611 (DE)

Application
EP 00810136 A 20000218

Priority
CH 48999 A 19990317

Abstract (en)
[origin: US6405411B1] The clasp comprises a coupling element with which the cheek plate elements adjacent to a closed position and comprising a coupling bolt for a closing device can be provisionally connected. The coupling element is a bracket which is mounted at its one end so that it can pivot on the coupling bolt of the one cheek plate element and which can be connected by its other end to the other cheek plate element in such a manner that this other end is movably mounted in the coupled position on the other cheek plate element.

IPC 1-7
B21D 39/04; F16L 13/14; B25B 27/02

IPC 8 full level
B21D 39/04 (2006.01); **B25B 27/10** (2006.01)

CPC (source: EP US)
B21D 39/04 (2013.01 - EP US); **B25B 27/10** (2013.01 - EP US); **Y10T 24/1412** (2015.01 - EP US); **Y10T 24/1418** (2015.01 - EP US); **Y10T 24/142** (2015.01 - EP US); **Y10T 24/1424** (2015.01 - EP US); **Y10T 29/49895** (2015.01 - EP US); **Y10T 29/53917** (2015.01 - EP US)

Cited by
AU2010272725B2; EP1535677A1; US8530961B2; WO2011006778A1

Designated contracting state (EPC)
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
US 6405411 B1 20020618; AT 4927 U1 20020125; AT E242668 T1 20030615; AU 2232600 A 20000921; DE 20004099 U1 20000504; DE 50002511 D1 20030717; EP 1036608 A1 20000920; EP 1036608 B1 20030611; PL 338945 A1 20000925

DOCDB simple family (application)
US 52659100 A 20000316; AT 00810136 T 20000218; AT 1762000 U 20000313; AU 2232600 A 20000317; DE 20004099 U 20000304; DE 50002511 T 20000218; EP 00810136 A 20000218; PL 33894500 A 20000310