

Title (en)

Method and apparatus for calibration of RF and gradient field time delays

Title (de)

Verfahren und Gerät zur Kalibrierung von zeitlichen Verzögerungen zwischen RF- und Gradienten-Feldern

Title (fr)

Méthode et appareil pour la calibration de retards en temps de champs RF et champs de gradients

Publication

EP 1039309 B1 20060823 (EN)

Application

EP 00302112 A 20000315

Priority

US 27446899 A 19990322

Abstract (en)

[origin: EP1039309A1] A technique is disclosed for calibrating time delays (112, 114) between RF and gradient frequency pulses (78, 110) in a magnetic resonance imaging system. The calibration procedure includes the formation of calibration images of a phantom positioned in the gradient field system. Calibration images are processed and compared to one another to determine deviation between locations in the gradient field system and the impact of radio frequency-to gradient waveform time delays on the deviations. Optimal time delays are identified which minimize the deviations between the calibration images. Multiple axes of the system may be calibrated through the use of symmetrical phantoms and similar pulse sequences of each axis. A spectral-spatial pulse sequence is employed bearing the calibration routine. <IMAGE>

IPC 8 full level

G01R 33/46 (2006.01); **G01R 33/58** (2006.01); **A61B 5/055** (2006.01)

CPC (source: EP US)

G01R 33/58 (2013.01 - EP US)

Cited by

CN113050007A; US7239143B2; WO03023432A1; WO2004104613A1

Designated contracting state (EPC)

DE NL

DOCDB simple family (publication)

EP 1039309 A1 20000927; EP 1039309 B1 20060823; DE 60030191 D1 20061005; DE 60030191 T2 20070712; JP 2000279396 A 20001010; JP 3890181 B2 20070307; US 6288545 B1 20010911

DOCDB simple family (application)

EP 00302112 A 20000315; DE 60030191 T 20000315; JP 2000077427 A 20000321; US 27446899 A 19990322