

Title (en)

Device for moving two alignment members alternatively in antiphase

Title (de)

Vorrichtung zur alternativen und gegenphasigen Bewegung von zwei Ausrichteinrichtungen

Title (fr)

Dispositif pour déplacer alternativement et en opposition de phase deux organes d'alignement

Publication

EP 1041030 B1 20030924 (FR)

Application

EP 00104209 A 20000301

Priority

CH 63099 A 19990401

Abstract (en)

[origin: EP1041030A2] Each of the two articulations between the drive rocker bar (12) and sliding shafts (3a, 4a) is formed by two coaxial contact surfaces (8a, 9a; 10, 11) of semi-circular cross section. Each articulation unit is fixed only to the rocker bar. The slides hav e.g. springs (6, 7) to keep all moving surfaces in contact.

IPC 1-7

B65H 31/38

IPC 8 full level

B31B 50/98 (2017.01); **B65G 57/00** (2006.01); **B65H 3/62** (2006.01)

CPC (source: EP US)

B65H 3/62 (2013.01 - EP US); **B65H 2403/532** (2013.01 - EP US); **B65H 2555/10** (2013.01 - EP US); **Y10T 74/18216** (2015.01 - EP US); **Y10T 74/18336** (2015.01 - EP US); **Y10T 74/2101** (2015.01 - EP US)

Designated contracting state (EPC)

AT DE FR IT NL

DOCDB simple family (publication)

EP 1041030 A2 20001004; **EP 1041030 A3 20020403**; **EP 1041030 B1 20030924**; AT E250547 T1 20031015; CH 693270 A5 20030515; DE 60005429 D1 20031030; DE 60005429 T2 20040715; JP 2000313523 A 20001114; JP 3423916 B2 20030707; US 6431017 B1 20020813

DOCDB simple family (application)

EP 00104209 A 20000301; AT 00104209 T 20000301; CH 63099 A 19990401; DE 60005429 T 20000301; JP 2000100470 A 20000403; US 52766900 A 20000317