

Title (en)
Lavatories

Title (de)
Toilette

Title (fr)
Toilettes

Publication
EP 1041205 A2 20001004 (EN)

Application
EP 00302410 A 20000324

Priority
• GB 9907028 A 19990327
• GB 9910051 A 19990501

Abstract (en)
Foul air is drawn off from within a lavatory pan (1) via a duct (6) by a pump (13) located above water-level of a close-coupled cistern (2). The duct (6) opens from around the inside of a flat ring-device (4) inserted between the cistern (2) and pan (1) as part of the flushing-water conduit (3) between them. The pump (13) is operated while the lavatory seat (15) is occupied or in response to manual operation of a switch and until the pan (1) is flushed. A modified pan (21) incorporating an in-built air duct (20) opening from the flushing-water conduit (22) within the pan-body, may be used instead. Also, where a pan (31) is flushed through a down-pipe (32), the air may be withdrawn via T-junction (34) coupled into the pipe (32) above the pan (31). <IMAGE>

IPC 1-7
E03D 9/05

IPC 8 full level
E03D 9/05 (2006.01)

CPC (source: EP)
E03D 9/05 (2013.01)

Cited by
SG120871A1; EP2239380A3; GB2552752A; GB2552752B; US8505123B2; US10612223B2

Designated contracting state (EPC)
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
EP 1041205 A2 20001004; GB 0007274 D0 20000517

DOCDB simple family (application)
EP 00302410 A 20000324; GB 0007274 A 20000327