

Title (en)
Masonry structure and associated reinforcement method

Title (de)
Mauerwerkstruktur und Verfahren zu deren Verstärkung

Title (fr)
Structure de maçonnerie et procédé de renforcement associé

Publication
EP 1045089 B1 20050209 (FR)

Application
EP 00401040 A 20000414

Priority
FR 9904842 A 19990416

Abstract (en)
[origin: EP1045089A1] The system may be used in old churches with stone vault ceilings (10) where the mortar between the stones (14) of the vault deteriorating. It pins the stones and holds them in position. Bores are drilled in each stone from the top surface (17) to withi short distance of the bottom surface (16) and a pin (19) is anchored in each bore. The top ends of the pins extend a considerable distance above the top surface of the vault. A synthetic mortar or cement (1 is poured onto the top surface of the vault, to a depth sufficient to cover the top ends of the pins. The layer of mortar is strong compression, when set, and extends into the spring of the arch (11) to transfer thrust to the wall of the building. The mix is chosen to give a coefficient of thermal expansion as near as possible equal to that of the stones of the vault.

IPC 1-7
E04G 23/02

IPC 8 full level
E04G 23/02 (2006.01)

CPC (source: EP)
E04G 23/0218 (2013.01); **E04G 23/0233** (2013.01); **E04G 2023/0251** (2013.01)

Cited by
RU169131U1; CZ305689B6; RU2471943C2; RU169130U1; CZ305270B6; RU171928U1; FR2817575A1; CN103397604A; CZ306367B6; CN106536824A; JP2017515028A; US10011962B2; WO2015166103A1

Designated contracting state (EPC)
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
EP 1045089 A1 20001018; EP 1045089 B1 20050209; AT E288979 T1 20050215; DE 60017965 D1 20050317; FR 2792354 A1 20001020; FR 2792354 B1 20071012

DOCDB simple family (application)
EP 00401040 A 20000414; AT 00401040 T 20000414; DE 60017965 T 20000414; FR 9904842 A 19990416