

Title (en)  
Supply for discharge lamps

Title (de)  
Versorgung für Entladungslampe

Title (fr)  
Alimentation pour lampe à décharge

Publication  
**EP 1045621 B1 20030115 (EN)**

Application  
**EP 00201246 A 20000405**

Priority  
IT MI990774 A 19990414

Abstract (en)  
[origin: EP1045621A1] An autotransformer (10) has a first output (10a) for a starting voltage and a second output (10b) for a working voltage lower than the starting voltage. The switching contacts (12) of a relay (24) connect a load of lamps (14) selectively to the first output or the second output of the autotransformer. A timer (T) is reset and started when it receives an input signal and activates a driver circuit (21) of the relay (24) when it reaches a predetermined count. To ensure a lower electrical-energy consumption and a reliable supply to the lamps even in the presence of conditions unfavourable to the maintenance of the operative state, a current detector (15) and a voltage detector (19) are provided, as well as comparators (18, 20) for resetting and restarting the timer (T) when the current absorbed by the lamp or the supply voltage of the lamps fall below respective predetermined values. <IMAGE>

IPC 1-7  
**H05B 41/36**

IPC 8 full level  
**H05B 41/18** (2006.01); **H05B 41/38** (2006.01)

CPC (source: EP)  
**H05B 41/18** (2013.01); **H05B 41/382** (2013.01)

Designated contracting state (EPC)  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)  
**EP 1045621 A1 20001018; EP 1045621 B1 20030115**; AT E231325 T1 20030215; DE 60001191 D1 20030220; DE 60001191 T2 20031009; IT 1312178 B1 20020409; IT MI990774 A1 20001014

DOCDB simple family (application)  
**EP 00201246 A 20000405**; AT 00201246 T 20000405; DE 60001191 T 20000405; IT MI990774 A 19990414