

Title (en)  
Method and device for leaf-stripping of tobacco

Title (de)  
Verfahren und Vorrichtung zum Entblättern von Tabak

Title (fr)  
Procédé et dispositif pour effeuiller le tabac

Publication  
**EP 1046350 A1 20001025 (FR)**

Application  
**EP 00390008 A 20000417**

Priority  
FR 9904980 A 19990420

Abstract (en)  
The process comprises of manually feeding the dried tobacco stalks (4) into the jaws of a leaf stripping machine (1) that includes two mobile elements (3,8). These force the plant material through guide and stripping members (5,6). An Independent claim is included for machinery for performing the leaf stripping procedure

Abstract (fr)  
La présente invention concerne un procédé et un dispositif pour l'effeuillage des pieds de tabac coupés et séchés. Cette effeuillage est généralement suivie d'un triage des feuilles selon l'étage foliaire. Le procédé selon l'invention consiste essentiellement à pincer les feuilles entre deux organes entraînés dans une direction parallèle à l'axe de la tige puis à immobiliser ladite tige de manière à ce que les feuilles se trouvent arrachées. Le dispositif comporte deux organes mobiles de pincement et d'arrachage des feuilles, un guide de tige (5) et une butée de tige (6).  
<IMAGE>

IPC 1-7  
**A24B 5/00**

IPC 8 full level  
**A24B 5/00** (2006.01)

CPC (source: EP)  
**A24B 5/00** (2013.01)

Citation (applicant)  
• US 4353377 A 19821012 - SEYMOUR SHAUN A  
• US 4373323 A 19830215 - JONES THOMAS F  
• FR 2301184 A1 19760917 - FERRET LUCIEN [FR]

Citation (search report)  
• [AD] FR 2715033 A1 19950721 - PERIGORD TABAC [FR], et al  
• [AD] US 4836220 A 19890606 - MIYAKE YASUHIKO [JP], et al  
• [AD] FR 2341280 A2 19770916 - FERRET LUCIEN [FR]

Cited by  
CN107080286A; FR2934470A1; FR2936936A1; WO2010012953A3

Designated contracting state (EPC)  
DE ES FR GR IT PT

DOCDB simple family (publication)  
**EP 1046350 A1 20001025**; FR 2792503 A1 20001027; FR 2792503 B1 20020322

DOCDB simple family (application)  
**EP 00390008 A 20000417**; FR 9904980 A 19990420