

Title (en)  
Panel testing apparatus and method

Title (de)  
Apparat und Verfahren zum Testen von Platten

Title (fr)  
Appareil et méthode pour tester des panneaux

Publication  
**EP 1046895 A3 20020116 (EN)**

Application  
**EP 00303032 A 20000411**

Priority  
US 29693999 A 19990422

Abstract (en)  
[origin: EP1046895A2] Apparatus and method for non-destructively testing the stiffness of wood panels having opposed panel surfaces and ends. The apparatus comprises a support framework (4) having infeed, centre and outfeed support assemblies (10,12,14) mounted to the framework (4) in spaced, successive positions. Each support assembly is adapted to contact the opposed panel surfaces of each panel to define a travel path along which the panel is advanced through the assembly. A first deflection member (17) is provided intermediate the infeed and centre support assemblies and is movable to contact one of the panel surfaces as each panel extends between the infeed and the centre support assemblies with one end of the panel being supported by the infeed support assembly and the opposite end being supported by the centre support assembly. The first deflection member (17) acts to bend the panel to a first pre-determined curvature. In a similar manner, there is a second deflection member (18) intermediate the centre and outfeed support assemblies movable to contact the same panel surface to bend the panel to a second pre-determined curvature. Load cells associated with the first and second deflection members (17,18) measure the force required to bend the panels to the pre-determined curvatures for calculation of the stiffness of the panels. The infeed, centre and outfeed support assemblies are movable relative to each other to position the support assemblies such that the travel paths through the support assemblies define a generally "C" shaped path through the apparatus that accommodates the curvatures that each panel adopts in travelling through the apparatus. The apparatus provides a compact panel testing unit by virtue of the novel "C" shaped travel path through the apparatus that is able to operate at the high speeds of a production line.

IPC 1-7  
**G01M 5/00; G01N 3/20; G07D 7/18**

IPC 8 full level  
**G01N 3/32 (2006.01); G01N 33/46 (2006.01); G07D 7/182 (2016.01); G01N 3/02 (2006.01)**

CPC (source: EP US)  
**G01N 3/32 (2013.01 - EP US); G01N 33/46 (2013.01 - EP US); G01N 2203/0023 (2013.01 - EP US); G01N 2203/0248 (2013.01 - EP US); G01N 2203/0282 (2013.01 - EP US)**

Citation (search report)  
• [A] US 5503024 A 19960402 - BECHTEL FRIEND K [US], et al  
• [A] EP 0326284 A2 19890802 - CZINNER ROBERT L  
• [A] US 4991446 A 19910212 - BECHTEL FRIEND K [US]  
• [A] EP 0521625 A1 19930107 - NCR INT INC [US]  
• [A] DE 2820959 A1 19781116 - INST TECH DREWNA  
• [A] GB 1025485 A 19660414 - POTLATCH FORESTS INC  
• [A] US 5892157 A 19990406 - SYRE HANS-RICHARD [DE]  
• [A] EP 0472282 A2 19920226 - CSR LTD [AU]  
• [A] PATENT ABSTRACTS OF JAPAN vol. 018, no. 539 (P - 1812) 13 October 1994 (1994-10-13)

Cited by  
CN108237612A

Designated contracting state (EPC)  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)  
**EP 1046895 A2 20001025; EP 1046895 A3 20020116; EP 1046895 B1 20060125;** AT E316649 T1 20060215; CA 2303458 A1 20001022;  
CA 2303458 C 20020507; DE 60025672 D1 20060413; DE 60025672 T2 20060720; PL 339642 A1 20001023; TR 200001034 A2 20001121;  
TR 200001034 A3 20001121; US 6055867 A 20000502

DOCDB simple family (application)  
**EP 00303032 A 20000411;** AT 00303032 T 20000411; CA 2303458 A 20000330; DE 60025672 T 20000411; PL 33964200 A 20000413;  
TR 200001034 A 20000417; US 29693999 A 19990422