

Title (en)

SOLID STATE ELECTRIC GENERATOR USING RADIONUCLIDE-INDUCED EXCITON PRODUCTION

Title (de)

ELEKTRISCHE GENERATOR MIT EINEM FESTKÖRPER IN DEM DURCH RADIONUKLIDE EXZITONEN ERZEUGT WERDEN

Title (fr)

GENERATEUR A SEMICONDUCTEUR UTILISANT LA PRODUCTION D'EXCITONS INDUIITE PAR RADIONUCLEIDES

Publication

EP 1048083 A1 20001102 (EN)

Application

EP 99903012 A 19990115

Priority

- US 9900380 W 19990115
- US 7166798 P 19980116

Abstract (en)

[origin: WO9936967A1] A heat and electrical energy conversion device using diamond or other single or polycrystalline substances as a storage medium. A radioactive isotope is impregnated into the diamond crystalline structure so that the interstitial voids between the carbon atoms of the diamond structure are each occupied by an atom of the radioactive isotope. However, other wide band-gap materials, such as the typical wide band-gap direct transition materials that include silicon carbide (SiC), gallium nitride (GaN), and aluminium nitride (AlN), also can be used, depending on the desired photoluminescence wavelengths. The crystal lattices produce electromagnetic radiation in response to charged particle irradiation, e.g., the EXCITON mechanism or emission due to color centers, defects or vacancies effect to provide a conversion of the emitted particles to photons, which subsequently are converted to electrical energy with photovoltaic devices. The devices can be assembled in to cells and the cells wired into modules.

IPC 1-7

H01L 31/00

IPC 8 full level

G21H 1/12 (2006.01); **G21H 3/00** (2006.01); **H01L 31/042** (2006.01); **H02N 6/00** (2006.01); **H02S 99/00** (2014.01)

CPC (source: EP)

G21H 1/12 (2013.01); **H02S 99/00** (2013.01); **Y02E 10/50** (2013.01)

Citation (search report)

See references of WO 9936967A1

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

WO 9936967 A1 19990722; AU 2313299 A 19990802; EP 1048083 A1 20001102; JP 2002510035 A 20020402

DOCDB simple family (application)

US 9900380 W 19990115; AU 2313299 A 19990115; EP 99903012 A 19990115; JP 2000540583 A 19990115