

Title (en)
Method for correcting the characteristic curve of a linear lambda sensor

Title (de)
Verfahren zur Korrektur der Kennlinie einer Breitband-Lambda-Sonde

Title (fr)
Méthode pour corriger la courbe caractéristique d'une sonde lambda linéaire

Publication
EP 1048834 A3 20020807 (DE)

Application
EP 00107491 A 20000406

Priority
DE 19919427 A 19990428

Abstract (en)
[origin: EP1048834A2] A lambda probe (LP) is fitted in an exhaust gas purifier for an internal combustion engine upstream from a catalytic convert
Determined in the phase for fuel cut-off in the overrun (FCO), the LP's signal level is assigned to the lambda value correspondi to the oxygen
concentration in the surrounding air. An increase in the LP's signal (1p) is taken into account during FCO. A desi value curve (2) for the LP shows no
carbon hydride emissions in the FCO.

IPC 1-7
F02D 41/14

IPC 8 full level
F02D 41/12 (2006.01); **F02D 41/14** (2006.01)

CPC (source: EP)
F02D 41/123 (2013.01); **F02D 41/1441** (2013.01); **F02D 41/1456** (2013.01); **F02D 41/1486** (2013.01); **F02D 41/1493** (2013.01)

Citation (search report)
• [XY] US 4676213 A 19870630 - ITSUJI TAKAYUKI [JP], et al
• [Y] DE 4322361 A1 19940105 - NIPPON DENSO CO [JP]
• [X] US 4753203 A 19880628 - YAMADA TETSUSYO [JP]
• [X] US 4909223 A 19900320 - ITUZI TAKAUKI [JP], et al
• [PDX] DE 19842425 A1 20000330 - SIEMENS AG [DE]

Cited by
EP1333171A1; FR2981697A1; DE102006000199B4; EP1748173A3; EP1143132A3; EP1624174A1; FR2874091A1; CN102102593A;
EP2336532A3; EP1961940A3; DE102009054751B4; US8499752B2; US9091226B2; WO2011038322A3; WO2008071500A1; WO2016098276A1;
WO2012175242A1; EP2786003B1; US8108130B2

Designated contracting state (EPC)
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
EP 1048834 A2 20001102; **EP 1048834 A3 20020807**; DE 19919427 A1 20001102; DE 19919427 C2 20010920

DOCDB simple family (application)
EP 00107491 A 20000406; DE 19919427 A 19990428