

Title (en)

Method and device for starting, braking and reversing of a two-stroke diesel engine

Title (de)

Verfahren und Vorrichtung zum Starten, Bremsen und Umsteuern eines Zweitakt-Dieselmotors

Title (fr)

Méthode et dispositif pour démarrage, freinage et inversion du sens de rotation d'un moteur Diesel à deux temps

Publication

EP 1048844 B1 20041013 (DE)

Application

EP 00810307 A 20000407

Priority

- EP 00810307 A 20000407
- EP 99810363 A 19990430

Abstract (en)

[origin: EP1048844A1] By relying on the swing angle of a piston shaft, compressed fluid such as compressed air is fed to one or more cylinders, so that a piston in a cylinder is accelerated or slowed down by the pressure (20) change resulting from this. A cylinder's outlet valve varied when opened and closed regarding the swing angle of the piston shaft.

IPC 1-7

F02N 9/04

IPC 8 full level

F02N 9/04 (2006.01); **F02D 13/04** (2006.01); **F02D 13/08** (2006.01); **F02D 27/00** (2006.01); **F02D 45/00** (2006.01); **F02B 3/06** (2006.01); **F02B 75/02** (2006.01)

CPC (source: EP KR)

F02B 25/00 (2013.01 - KR); **F02N 9/04** (2013.01 - EP); **F02B 3/06** (2013.01 - EP); **F02B 2075/025** (2013.01 - EP); **F02F 2007/0097** (2013.01 - EP)

Cited by

EP1653078A1; DE102004035301B4; WO2012032216A1

Designated contracting state (EPC)

DE DK FR IT NL

DOCDB simple family (publication)

EP 1048844 A1 20001102; EP 1048844 B1 20041013; CN 1201077 C 20050511; CN 1272594 A 20001108; DE 50008185 D1 20041118; DK 1048844 T3 20041108; JP 2000320437 A 20001121; KR 100635441 B1 20061017; KR 20000077086 A 20001226; NO 20002237 D0 20000428; NO 20002237 L 20001031; NO 323742 B1 20070702; PL 199244 B1 20080829; PL 339895 A1 20001106

DOCDB simple family (application)

EP 00810307 A 20000407; CN 00108153 A 20000429; DE 50008185 T 20000407; DK 00810307 T 20000407; JP 2000127439 A 20000427; KR 20000022182 A 20000426; NO 20002237 A 20000428; PL 33989500 A 20000426