

Title (en)

Color paper with exceptional reciprocity performance

Title (de)

Farbpapier mit aussergewöhnlicher Reziprozitätsleistung

Title (fr)

Papier couleur avec une performance de réciprocité exceptionnelle

Publication

EP 1048978 A1 20001102 (EN)

Application

EP 00201365 A 20000417

Priority

- US 29954899 A 19990426
- US 32872399 A 19990609

Abstract (en)

The invention relates to a negative working reflective base photographic element comprising support material wherein said support material comprises a paper base and overlaying said paper base are full color photographic silver halide containing imaging layers wherein said photographic element has an exposure range of between 1000 nanoseconds and 0.5 seconds when there is a density loss of no more than 10 percent as a function of the red shoulder color record, wherein said photographic element has an exposure range of between 1000 nanoseconds and 0.5 seconds when there is a density loss of no more than 8 percent as a function of the green shoulder color record, wherein said photographic element has an exposure range of between 1000 nanoseconds and 0.5 seconds when there is a density loss of no more than 5 percent as a function of the blue shoulder color record, wherein said photographic element has an exposure range of between 1000 nanoseconds and 0.5 seconds when there is a density loss of no more than 6 percent as a function of the red Dmax color record, wherein said photographic element has an exposure range of between 1000 nanoseconds and 0.5 seconds when there is a density loss of no more than 9 percent as a function of the green Dmax color record, wherein said photographic element has an exposure range of between 1000 nanoseconds and 0.5 seconds when there is a density loss of no more than 5 percent as a function of the blue Dmax color record, wherein said photographic element has an exposure range of between 1000 nanoseconds and 0.5 seconds when there is a density loss of no more than 9 percent as a function of the red inmax color record, wherein said photographic element has an exposure range of between 1000 nanoseconds and 0.5 seconds when there is a density loss of no more than 10 percent as a function of the green inmax color record, and wherein said photographic element has an exposure range of between 1000 nanoseconds and 0.5 seconds when there is a density loss of no more than 5 percent as a function of the blue inmax color record. <IMAGE>

IPC 1-7

G03C 7/30; **G03C 1/09**

IPC 8 full level

G03C 7/20 (2006.01); **G03C 1/09** (2006.01); **G03C 7/00** (2006.01); **G03C 7/30** (2006.01)

CPC (source: EP)

G03C 1/09 (2013.01); **G03C 7/3041** (2013.01); **G03C 1/08** (2013.01); **G03C 2200/42** (2013.01)

Citation (search report)

- [X] US 5728516 A 19980317 - EDWARDS JAMES LAWRENCE [US], et al
- [DX] US 5783373 A 19980721 - MYDLARZ JERZY Z [US], et al
- [DX] US 5474888 A 19951212 - BELL ERIC L [US]
- [DA] US 5457021 A 19951010 - OLM MYRA T [US], et al
- [DA] EP 0774689 A1 19970521 - EASTMAN KODAK CO [US]

Cited by

EP1376223A3; WO2004010217A1; US7083905B2; US7226727B2; US7344828B2

Designated contracting state (EPC)

BE CH DE FR GB LI NL

DOCDB simple family (publication)

EP 1048978 A1 20001102; CN 1271869 A 20001101; JP 2000321730 A 20001124

DOCDB simple family (application)

EP 00201365 A 20000417; CN 00106989 A 20000426; JP 2000131544 A 20000426