

Title (en)  
BLOCKING DEVICE FOR A DOOR PROVIDED WITH A DOOR CLOSER

Title (de)  
FESTSTELLVORRICHTUNG FÜR EINE MIT EINEM TÜRSCHLIESSER VERSEHENE TÜR

Title (fr)  
DISPOSITIF DE BLOCAGE POUR PORTE POURVUE D'UN FERME-PORTE

Publication  
**EP 1051558 B1 20020320 (DE)**

Application  
**EP 99932418 A 19990130**

Priority  
• DE 9900246 W 19990130  
• DE 19803789 A 19980130  
• DE 19901773 A 19990118

Abstract (en)  
[origin: WO9939069A1] The invention relates to a blocking device for a door provided with a door closer (3). A sliding arm (32) is coupled with the end thereof on the door leaf or on the door frame. The other end of the sliding arm is guided with a glider (33) inside a track (4) in a moveable manner, said track being arranged on the door frame or door leaf. The glider (33) interacts with a stop (61) which is arranged in the track (4) and which is pushed in the movement area of the glider (33) by the action of a spring element (6). The stop (61) interacts with an electrically switchable control element (8). According to the invention, the control element (8) comprises a piezo-electric element, a magnetostrictive element, a thermostrictive element, a shape-memory element or a comparable actuator. In order to prevent deviation, the spring element (6) is alternatively supported in or released from a support point by a blocking element (7) which is preferably guided in an axial direction in the track, whereby the blocking element (7) interacts with the control element (8). The movement of the blocking element (7) is blocked in a first position of the control element (8) and, as a result, the spring element (6) is blocked. As a consequence, the glider (33) which is guided in the track (4) can not deflect the stop (61), and the door leaf remains blocked. The movement of the blocking element (7) is permitted in a second position of the control element (8). The action of a recoil spring (9) causes the blocking element (7) to move out of the blocking position thereof and to release the spring element (6). The glider (33) can thus deflect the stop (61) against the force of the spring element (6) and the door leaf closes.

IPC 1-7  
**E05C 17/28**; **E05B 47/00**

IPC 8 full level  
**E05B 47/00** (2006.01); **E05C 17/28** (2006.01)

CPC (source: EP)  
**E05B 47/00** (2013.01); **E05B 47/0009** (2013.01); **E05C 17/28** (2013.01); **E05F 2003/228** (2013.01); **E05Y 2201/43** (2013.01); **E05Y 2201/46** (2013.01); **E05Y 2800/67** (2013.01); **E05Y 2900/132** (2013.01)

Cited by  
US9995076B1

Designated contracting state (EPC)  
AT BE CH DE ES FI FR GB IT LI NL PT SE

DOCDB simple family (publication)  
**WO 9939069 A1 19990805**; AT E214773 T1 20020415; AU 3246999 A 19990816; DE 19980135 D2 20010802; DE 29980014 U1 20010111; EP 1051558 A1 20001115; EP 1051558 B1 20020320

DOCDB simple family (application)  
**DE 9900246 W 19990130**; AT 99932418 T 19990130; AU 3246999 A 19990130; DE 19980135 T 19990130; DE 29980014 U 19990130; EP 99932418 A 19990130