

Title (en)
Hydraulic closing-device for the lateral extrusion of workpieces

Title (de)
Hydraulische Schliessvorrichtung zum Querfliesspressen von Werkstücken

Title (fr)
Dispositif de fermeture hydraulique pour l'extrusion latérale de pièces

Publication
EP 1053801 A3 20020515 (DE)

Application
EP 00109492 A 20000504

Priority
DE 19922659 A 19990518

Abstract (en)
[origin: EP1053801A2] The device has two relatively moveable lockable molds (22,42). The first mold is held on a hydraulic piston (16) moving in a cylinder (6), carrying a first press die (20). The second mold is stationary and positioned on a second hydraulic cylinder (26), the second press die (40) is located on a second hydraulic piston (36). During impact extrusion of a component, the second piston charged by a pressure medium displaced by the first piston. The first hydraulic cylinder is positioned on press ram.

IPC 1-7
B21J 5/00; **B21J 9/12**; **B21C 23/21**

IPC 8 full level
B21C 23/21 (2006.01); **B21J 5/00** (2006.01); **B21J 5/02** (2006.01); **B21J 9/12** (2006.01)

CPC (source: EP)
B21C 23/21 (2013.01); **B21J 5/02** (2013.01); **B21J 9/12** (2013.01)

Citation (search report)
• [A] EP 0298457 A2 19890111 - AIDA ENG LTD [JP]
• [A] US 4977773 A 19901218 - MITO YOSHIKI [JP], et al

Cited by
CN112935167A

Designated contracting state (EPC)
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
EP 1053801 A2 20001122; **EP 1053801 A3 20020515**; **EP 1053801 B1 20040303**; AT E260721 T1 20040315; BR 0003064 A 20010130; DE 19922659 A1 20001207; DE 19922659 B4 20050210; DE 50005478 D1 20040408

DOCDB simple family (application)
EP 00109492 A 20000504; AT 00109492 T 20000504; BR 0003064 A 20000518; DE 19922659 A 19990518; DE 50005478 T 20000504