

Title (en)  
Panic door lock

Title (de)  
Antipaniktürschloss

Title (fr)  
Serrure antipanique

Publication  
**EP 1055790 A2 20001129 (DE)**

Application  
**EP 00109982 A 20000511**

Priority  
ES 9901006 A 19990513

Abstract (en)

The slide rails (9,10) are actuated by top (11) and/or bottom (12) levers having two arms (13,14) in U form joined by crossb and arranged to pivot via horizontal frame bolt (16). Arm (13) edge bears on a reversible cam (8) as keyed crossways onto an actuator shaft (7) coupled to a swivel arm (3,4). The far edge of the arm (13) opposite the first edge can be contacted with the cross part (19) of the frame (5) at the end of the arm (13) swivel movement as initiated by bar (2) depression towards the door thus opening the lock. Arm (14) on the other hand has a radial tip which rides with play in a rail (9,10) slotway. The crossbar the frame (5) uses a third edge contacting a pin extending from the top or bottom edges of the general bolt (20).

Abstract (de)

Ein Antipanik-Schloß weist ein in Richtung auf eine Tür (1) verschwenkbares Betätigungsselement (2;24) für einen in einer Halterung (5,6) angeordneten Betätigungsmechanismus für einen horizontalen Riegel (20) und vertikale obere und untere Gleitschienen (9,10) zur Betätigung oberer und unterer Riegel (21,22) auf. Die Gleitschienen sind durch obere und untere allgemein U-förmige Schwenkhebel (11,12) mit ersten und zweiten Armen (13,14) betätigbar, die durch einen Querteil (15) verbunden und auf einem horizontalen Bolzen (16) eines Rahmens (5a) der Halterung (5) gelagert sind. Der erste Arm weist eine erste Kante (13a), die gegen einen Betätigungsteil (8a) eines durch das Betätigungsselement verschwenkbaren Nockens (8) anliegt, und eine zweite Kante (13b) auf, die an einem Querteil (19) des Rahmens (5a) am Ende eines Dreharbeitshebels des ersten Armes anschlägt. Der zweite Arm weist eine sich in Radialrichtung erstreckende Spitze auf, die sich in einen Schlitz (18) in den Gleitschienen erstreckt. Der Querteil weist eine dritte Kante (15a) auf, die an einem Zapfen (20a) zur Anlage kommt, der sich von dem horizontalen Riegel erstreckt. <IMAGE>

IPC 1-7  
**E05B 65/10**

IPC 8 full level  
**E05B 65/10** (2006.01)

CPC (source: EP)  
**E05B 65/1066** (2013.01); **E05B 65/1006** (2013.01)

Cited by  
EP1318257A3; US2014130624A1; EP2078810A4

Designated contracting state (EPC)  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)  
**EP 1055790 A2 20001129; EP 1055790 A3 20031001; EP 1055790 B1 20050209**; AT E288984 T1 20050215; DE 50009450 D1 20050317;  
ES 2168171 A1 20020601; ES 2168171 B1 20030501

DOCDB simple family (application)  
**EP 00109982 A 20000511**; AT 00109982 T 20000511; DE 50009450 T 20000511; ES 9901006 A 19990513