

Title (en)

METHOD AND APPARATUS FOR MOUNTING A BEARING

Title (de)

VERFAHREN UND VORRICHTUNG ZUM ANBAU EINES LAGERS

Title (fr)

PROCEDE ET DISPOSITIF DE MONTAGE D'UNE PORTEE

Publication

EP 1058773 A1 20001213 (EN)

Application

EP 99908555 A 19990226

Priority

- US 9904353 W 19990226
- US 7625598 P 19980227

Abstract (en)

[origin: WO9943927A1] A method and apparatus for mounting a bearing (20) on a shaft (22). An intermediate member (24) is mounted on the shaft (22). An inner race (26) of the bearing is mounted onto the intermediate member (24). Two separable compression members (52, 54) are mounted on the outer diameter of the inner race (26). The compression members (52, 54) are mounted with an interference fit, thus inducing a state of compression in the inner race. The intermediate member (24) is radially compliant and compensates for thermal growth of the shaft (22) in excess of the thermal growth of the inner race (26). The state of compression in the inner race (26) persists to about 1000 DEG F. In one embodiment, the present invention includes an inner race (26) fabricated from a material with low fracture toughness or for which a state of compression is desirable, such as a ceramic material.

IPC 1-7

F01D 25/16; F16C 33/34; B23P 15/00; D01H 7/20

IPC 8 full level

B23P 15/00 (2006.01); **D01H 7/20** (2006.01); **F01D 25/16** (2006.01); **F16C 33/62** (2006.01); **F16C 35/073** (2006.01)

CPC (source: EP US)

F01D 25/16 (2013.01 - EP US); **F16C 33/62** (2013.01 - EP US); **F16C 35/073** (2013.01 - EP US); **F05D 2300/2283** (2013.01 - EP US); **F16C 19/26** (2013.01 - EP US); **F16C 2206/60** (2013.01 - EP US); **F16C 2360/23** (2013.01 - EP US); **F16D 1/0835** (2013.01 - EP US)

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

WO 9943927 A1 19990902; AU 2795899 A 19990915; CA 2321641 A1 19990902; EP 1058773 A1 20001213; EP 1058773 A4 20020502; JP 2002505396 A 20020219; US 6261061 B1 20010717

DOCDB simple family (application)

US 9904353 W 19990226; AU 2795899 A 19990226; CA 2321641 A 19990226; EP 99908555 A 19990226; JP 2000533649 A 19990226; US 56320400 A 20000502