

Title (en)

SILENT DISCHARGE TUBE AND ITS USE METHOD

Title (de)

STILLE ENTLADUNGS-RÖHRE UND ANWENDUNGS-VERFAHREN DERSELBEN

Title (fr)

TUBE A DECHARGE SILENCIEUX ET PROCEDE D'UTILISATION

Publication

EP 1059659 A1 20001213 (EN)

Application

EP 99961407 A 19991227

Priority

- JP 9907323 W 19991227
- JP 37247198 A 19981228

Abstract (en)

The power consumption of a silent discharge lamp having a structure in which an inner tube is disposed in the interior of an outer tube is reduced. In addition, the lifetime is extended. For this purpose, in a silent discharge lamp including: a discharge vessel which has an outer tube and an inner tube, the inner tube being disposed in an interior of the outer tube, and in which a space that is formed by being surrounded by an inner face of the outer tube and an outer face of the inner tube is filled with a discharge gas; an outside electrode provided on an outer face of the outer tube; and an inside electrode provided on an inner face of the inner tube, one of the outside electrode and the inside electrode is provided over all circumference of a tube, and the other one is provided in a part of a tube circumference, thereby allowing discharge to be performed in the part of the tube circumference. The electrode is moved at the end of the lifetime, so that a face in which discharge is not caused is newly used. <IMAGE>

IPC 1-7

H01J 65/00

IPC 8 full level

H01J 61/30 (2006.01); **H01J 65/04** (2006.01)

CPC (source: EP KR)

H01J 61/30 (2013.01 - EP); **H01J 65/00** (2013.01 - KR); **H01J 65/046** (2013.01 - EP)

Cited by

EP1519407A3; US7411349B2; US8237364B2; CN109786207A; EP3483918A3; WO2009068073A1; WO2006072892A3

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

EP 1059659 A1 20001213; **EP 1059659 A4 20020313**; KR 100797904 B1 20080124; KR 20010085206 A 20010907; WO 0041215 A1 20000713

DOCDB simple family (application)

EP 99961407 A 19991227; JP 9907323 W 19991227; KR 20007009576 A 20000828