

Title (en)

Method and equipment for removing and/or cutting off bobs when die-casting

Title (de)

Verfahren und Vorrichtung zum Entfernen und/oder Abschneiden von Anschnitten beim Druckgiessen

Title (fr)

Procédé et dispositif pour enlever et/ou decouper des attaques pendant la coulée en coquille

Publication

**EP 1063036 A1 20001227 (EN)**

Application

**EP 99830392 A 19990622**

Priority

EP 99830392 A 19990622

Abstract (en)

The invention concerns equipment for removing the bobs (runners, gates)(16,17) from die-cast pieces (11). It is made up of hubs (18,19) mounted crossways in the parts or half dies (12a,12b) of the die, facing the bobs at the height of the attachment zones (16',17') of the latter to the piece. The hubs are moved to push away and detach the feedheads after the piece has been moulded and before the die is opened to lift off the said piece.  
<IMAGE>

IPC 1-7

**B22D 17/20**

IPC 8 full level

**B22D 17/20** (2006.01)

CPC (source: EP)

**B22D 17/2076** (2013.01)

Citation (search report)

- [X] DE 976942 C 19640820 - NAT LEAD CO
- [A] US 4799534 A 19890124 - UENO TOYOAKI [JP], et al
- [A] PATENT ABSTRACTS OF JAPAN vol. 016, no. 299 (M - 1274) 2 July 1992 (1992-07-02)
- [A] PATENT ABSTRACTS OF JAPAN vol. 009, no. 294 (M - 431) 20 November 1985 (1985-11-20)
- [A] PATENT ABSTRACTS OF JAPAN vol. 009, no. 235 (M - 415) 21 September 1985 (1985-09-21)
- [A] PATENT ABSTRACTS OF JAPAN vol. 018, no. 396 (M - 1644) 25 July 1994 (1994-07-25)

Cited by

CN110076321A

Designated contracting state (EPC)

AT BE CH DE DK ES FI LI

DOCDB simple family (publication)

**EP 1063036 A1 20001227**

DOCDB simple family (application)

**EP 99830392 A 19990622**