

Title (en)

Method for driving a discharge lamp

Title (de)

Verfahren zum Betrieb einer Entladungslampe

Title (fr)

Procédé pour alimenter une lampe à décharge

Publication

**EP 1063682 B1 20040616 (DE)**

Application

**EP 00107629 A 20000408**

Priority

DE 19928438 A 19990623

Abstract (en)

[origin: EP1063682A1] A first, dielectrically-limited discharge is produced by forming xenon excimer under UV radiation. A second discharge is produced without dielectric limitation. This is a low pressure xenon discharge emitting UV radiation. Fluorescent materials (2) convert radiation from both discharges, into visible light.

IPC 1-7

**H01J 61/92**; H01J 65/04; H01J 61/16; H01J 61/78

IPC 8 full level

**H05B 41/24** (2006.01); **H01J 61/16** (2006.01); **H01J 61/78** (2006.01); **H01J 61/92** (2006.01); **H01J 65/00** (2006.01); **H01J 65/04** (2006.01); **H05B 41/392** (2006.01)

CPC (source: EP US)

**H01J 61/16** (2013.01 - EP US); **H01J 61/78** (2013.01 - EP US); **H01J 61/92** (2013.01 - EP US); **H01J 65/046** (2013.01 - EP US)

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

**EP 1063682 A1 20001227**; **EP 1063682 B1 20040616**; AT E269587 T1 20040715; CA 2312132 A1 20001223; DE 19928438 A1 20001228; DE 50006799 D1 20040722; ES 2223333 T3 20050301; JP 2001052890 A 20010223; JP 4339492 B2 20091007; US 6259214 B1 20010710

DOCDB simple family (application)

**EP 00107629 A 20000408**; AT 00107629 T 20000408; CA 2312132 A 20000622; DE 19928438 A 19990623; DE 50006799 T 20000408; ES 00107629 T 20000408; JP 2000186151 A 20000621; US 59338300 A 20000614