

Title (en)

Reverse spreading device, timing detecting device, channel estimating device, frequency error measurement method and automatic frequency control method

Title (de)

Einrichtung zum Umkehrspreitzen des Spectrum, Einrichtung zur Zeitpunktdetektion, Kanalschätzer, Frequenzmessung und automatische Frequenzregelung

Title (fr)

Dispositif à étalment inverse de spectre, dispositif de détection temporelle, estimateur de canal, procédé pour mesurer l'erreur de fréquence et de pour commander automatiquement la fréquence

Publication

EP 1063779 B9 20050119 (EN)

Application

EP 00250193 A 20000623

Priority

- JP 17709899 A 19990623
- JP 31390099 A 19991104

Abstract (en)

[origin: EP1063779A2] A reverse spreading device is provided which is capable of performing timing detection and channel estimation even in a large frequency offset environment without great increases in its circuit scale and its power consumption and of expanding a range being within an AFC (Automatic Frequency Control) for a frequency offset. A multiplication is made by multipliers between complex base band signals and spread codes and then resulting n-pieces of multiplied values are integrated by m-pieces of adders for every k-pieces of multiplied values to produce m-pieces of complex intermediate signals before obtaining complex symbols. A probability of correct synchronization is increased by providing a frequency offset to m-pieces of complex intermediate signals using phase rotators (311 to 31m) to compensate for rotation within one symbol period and to obtain a great spreading gain. A range being within the ACF for the frequency offset is expanded since a phase error is corrected before the production of the complex symbol signals. <IMAGE>

IPC 1-7

H04B 1/707

IPC 8 full level

H04B 1/707 (2011.01); **H04B 1/7087** (2011.01); **H04B 7/216** (2006.01); **H04L 27/00** (2006.01)

CPC (source: EP US)

H04B 1/707 (2013.01 - EP US); **H04L 27/0014** (2013.01 - EP US); **H04L 2027/0065** (2013.01 - EP US)

Cited by

EP1931080A3; EP1259021A3; EP1471703A3; EP1931080A2; US7496160B2

Designated contracting state (EPC)

DE GB SE

DOCDB simple family (publication)

EP 1063779 A2 20001227; **EP 1063779 A3 20030423**; **EP 1063779 B1 20041013**; **EP 1063779 B9 20050119**; CN 1119881 C 20030827; CN 1279545 A 20010110; DE 60014779 D1 20041118; DE 60014779 T2 20051013; JP 2001069040 A 20010316; JP 3329383 B2 20020930; US 7315590 B1 20080101

DOCDB simple family (application)

EP 00250193 A 20000623; CN 00109446 A 20000623; DE 60014779 T 20000623; JP 31390099 A 19991104; US 60255800 A 20000623