

Title (en)
METHOD FOR POSITIONING ENGRAVING MEMBERS

Title (de)
VERFAHREN ZUM POSITIONIEREN VON GRAVIERORGANEN

Title (fr)
PROCEDE DE POSITIONNEMENT D'ORGANES DE GRAVURE

Publication
EP 1068076 A1 20010117 (DE)

Application
EP 99924764 A 19990403

Priority
• DE 9901014 W 19990403
• DE 19814939 A 19980403

Abstract (en)
[origin: DE19814939A1] The invention relates to a method and device for positioning engraving members in an electronic engraving machine in order to engrave printing cylinders for rotogravure. At least two engraving billets (A,B,C) of the printing cylinder (1) are arranged next to each other in the direction of the printing cylinder (1) axis, each having a given width (SB), and are engraved as cup-shapes by an associated engraving member (3). Before engraving, the axial distances separating the engraving members (3) have to be adjusted according to the required width of the billets (SB). In order to save time, the axial distances between the engraving members (3) are initially adjusted in an approximate manner by hand. Axial reference position marks whose axial distances correspond to the width of the billets (SB) are produced in a device (20). The engraving members (3) also have axial position marks (19). When approximate positioning occurs, the engraving members (3) are displaced manually until their position marks (19) coincide with the assigned reference position marks. The engraving members (3) are finely positioned once approximate manual positioning has occurred.

IPC 1-7
B41C 1/04; H04N 1/047

IPC 8 full level
B41C 1/045 (2006.01); **B41C 1/02** (2006.01); **B41C 1/18** (2006.01)

CPC (source: EP US)
B41C 1/02 (2013.01 - EP US); **Y10T 409/303752** (2015.01 - EP US)

Citation (search report)
See references of WO 9951436A1

Designated contracting state (EPC)
BE DE ES FR GB IT NL

DOCDB simple family (publication)
DE 19814939 A1 19991007; EP 1068076 A1 20010117; JP 2002510570 A 20020409; US 6540453 B1 20030401; WO 9951436 A1 19991014

DOCDB simple family (application)
DE 19814939 A 19980403; DE 9901014 W 19990403; EP 99924764 A 19990403; JP 2000542179 A 19990403; US 64761700 A 20001103