

Title (en)

TYRE WITH BEARING INSIDE STRUCTURE AND DIFFERENTIATED INNER TUBES

Title (de)

REIFEN MIT INNENSTÜTZSTRUKTUR UND MEHREREN SCHLÄUCHEN

Title (fr)

PNEU MUNI D'UNE STRUCTURE PORTEUSE INTERNE ET DE CHAMBRES A AIR INTERNES DIFFERENCIEES

Publication

**EP 1071566 A1 20010131 (EN)**

Application

**EP 99917057 A 19990421**

Priority

- IT 9900099 W 19990421
- IT IM980002 A 19980423

Abstract (en)

[origin: WO9954154A1] The tyre is formed by a rubber structure with harmonic steel wire frame, which do not allow lateral deformation, forcing the tyre to get flabby on the vertical standing in case of puncture. Furthermore the above mentioned structure is divided into separate inner tubes, connected by "non-return" air in-flowing valves, which limit tyre puncture only to small sectors and maintain lift avoiding explosion. The inside structure, supporting statically the tyre, let it keep shape rigidity, which allows to work at lower air pressures with bigger sections, so recovering partially tyre cushion function. This system gives to the tyre an optimum rigidity level, in non-lowered tyres and with traditional rims too.

IPC 1-7

**B60C 5/22**; **B60C 17/01**

IPC 8 full level

**B60C 5/00** (2006.01); **B60C 5/22** (2006.01); **B60C 17/01** (2006.01)

CPC (source: EP)

**B60C 5/22** (2013.01); **B60C 5/24** (2013.01)

Citation (search report)

See references of WO 9954154A1

Designated contracting state (EPC)

DE ES FR GB IT

DOCDB simple family (publication)

**WO 9954154 A1 19991028**; AU 3532999 A 19991108; EP 1071566 A1 20010131; IT 1306537 B1 20010611; IT IM980002 A1 19980723

DOCDB simple family (application)

**IT 9900099 W 19990421**; AU 3532999 A 19990421; EP 99917057 A 19990421; IT IM980002 A 19980423