

Title (en)

DEVICE FOR ADJUSTING THE PHASE POSITION OF A SHAFT

Title (de)

VERSTELLVORRICHTUNG ZUM VERSTELLEN DER PHASENHALTE EINER WELLE

Title (fr)

DISPOSITIF POUR LE REGLAGE DE LA POSITION DE PHASE D'UN ARBRE

Publication

**EP 1078148 B1 20030514 (DE)**

Application

**EP 98929296 A 19980512**

Priority

EP 9802759 W 19980512

Abstract (en)

[origin: WO9958821A1] The device (1) for adjusting the phase position of a shaft, especially a camshaft (2) that can be rotated by a drive shaft, more particularly a crankshaft, by means of a transmission device with at least one transmission wheel (6'), is configured as a rotary piston machine according to the orbit principle. The inventive device adjusts the rotary position of the transmission wheel (6') in relation to the shaft. The rotary piston machine comprises a stator (5) with inner teeth (5a), an annular rotary piston (4) with outer teeth (4a) that engage with the inner teeth (5a) of the stator, a driven part (3) that can be rotated by means of the rotary piston (4) and a valve device (8-12). In order to control the movement of the rotary piston, the valve device (8-12) enables rotating partial areas of the working area (7) between the stator (5) and the rotary piston (4) to be joined to a fluid supply device at high or low pressure. The fluid supply device comprises a control mechanism, a phase position detector and at least one control valve. It enables a theoretical phase position to be adjusted by actuating the valve in a corresponding manner. Fluidic connection to the adjustment device occurs by means of two angular rotational connections (14a, 14b).

IPC 1-7

**F01L 1/34; F01L 1/344; F01L 1/352**

IPC 8 full level

**F01L 1/34** (2006.01); **F01L 1/344** (2006.01); **F01L 1/352** (2006.01); **F03C 2/22** (2006.01)

CPC (source: EP KR US)

**F01L 1/34** (2013.01 - EP KR US); **F01L 1/344** (2013.01 - EP US); **F01L 1/352** (2013.01 - EP US)

Designated contracting state (EPC)

AT BE CH DE DK ES FI FR GB GR IE IT LI LU NL PT SE

DOCDB simple family (publication)

**WO 9958821 A1 19991118**; AT E240452 T1 20030515; AU 7911398 A 19991129; BR 9815968 A 20011023; CA 2330144 A1 19991118; CN 1292845 A 20010425; DE 59808397 D1 20030618; EP 1078148 A1 20010228; EP 1078148 B1 20030514; HU P0101674 A2 20010828; HU P0101674 A3 20020128; JP 2002514705 A 20020521; KR 20010043542 A 20010525; SK 16982000 A3 20010409; US 6386165 B1 20020514

DOCDB simple family (application)

**EP 9802759 W 19980512**; AT 98929296 T 19980512; AU 7911398 A 19980512; BR 9815968 A 19980512; CA 2330144 A 19980512; CN 98814029 A 19980512; DE 59808397 T 19980512; EP 98929296 A 19980512; HU P0101674 A 19980512; JP 2000548594 A 19980512; KR 20007012654 A 20001113; SK 16982000 A 19980512; US 70008501 A 20010104