

Title (en)

METHOD FOR MACHINING WORKPIECES AND MACHINE TOOL

Title (de)

VERFAHREN ZUM BEARBEITEN VON WERKSTÜCKEN SOWIE WERKZEUGMASCHINE

Title (fr)

PROCEDE D'USINAGE DE PIECES ET MACHINE-OUTIL

Publication

**EP 1082189 A1 20010314 (DE)**

Application

**EP 99919018 A 19990517**

Priority

- EP 99919018 A 19990517
- CH 9900207 W 19990517
- EP 98810464 A 19980519

Abstract (en)

[origin: EP0958884A1] A laser beam (5) is guided parallel to and into the principal axis (L), or is guided directly within a machine tool axis; at least one laser machining head (K) is mechanically displaceable into the axis of a spindle so either the head (K) or a cutting tool is inserted into tool holder(s) is used without alteration or replacement of the workpiece mounting. A parking position (P) is foreseen within the machine tool (13) for the laser machining head and some of the beam guide tubes (12). The laser machining head is designed so its optical axis (X-X) is rigid and is oriented coaxially with the principal axis (L) of the machine tool. The laser beam is introduced into this head either coaxially or from a side.

IPC 1-7

**B23K 26/08**; **B23P 23/02**

IPC 8 full level

**B23K 26/06** (2006.01); **B23K 26/08** (2006.01); **B23P 23/02** (2006.01)

CPC (source: EP US)

**B23K 26/0093** (2013.01 - EP US); **B23P 23/02** (2013.01 - EP US); **B23Q 3/15573** (2013.01 - US); **Y10T 483/10** (2015.01 - EP US); **Y10T 483/17** (2015.01 - EP US)

Citation (search report)

See references of WO 9959765A1

Designated contracting state (EPC)

AT CH DE ES FR GB IE IT LI LU

DOCDB simple family (publication)

**EP 0958884 A1 19991124**; AU 3697099 A 19991206; EP 1082189 A1 20010314; JP 2002515344 A 20020528; US 6593541 B1 20030715; WO 9959765 A1 19991125

DOCDB simple family (application)

**EP 98810464 A 19980519**; AU 3697099 A 19990517; CH 9900207 W 19990517; EP 99919018 A 19990517; JP 2000549418 A 19990517; US 70085700 A 20001117