

Title (en)
METHODS AND APPARATUS FOR CONFOCAL INTERFERENCE MICROSCOPY USING WAVENUMBER DOMAIN REFLECTOMETRY AND BACKGROUND AMPLITUDE REDUCTION AND COMPENSATION

Title (de)
VERFAHREN UND APPARATEN FÜR KONFOKAL-INTERFERENZ-MIKROSKOPIE MITTELS WELLENNUMMERGEBIETSREFLEKTOMETRIE UND REDUKTION UND KOMPENSATION DES HINTERGRUNDS

Title (fr)
PROCEDES ET DISPOSITIFS DE MICROSCOPIE CONFOCALE D'INTERFERENCES AU MOYEN D'UNE REFLECTOMETRIE A DOMAINE DE NOMBRE D'ONDES ET D'UNE REDUCTION ET COMPENSATION D'AMPLITUDE D'ARRIERE-PLAN

Publication
EP 1084378 A1 20010321 (EN)

Application
EP 99928339 A 19990526

Priority

- US 9911601 W 19990526
- US 8910598 A 19980602
- US 12505799 P 19990318

Abstract (en)
[origin: WO9963300A1] An in-focus image of a region within and/or on an object (112) is discriminated from an out-of-focus image so as to reduce errors in image information of the object by producing a probe beam (P22B) and a reference beam (R22B) from a broadband point source (90), producing antisymmetric spatial properties in the reference beam (R32B), converting the probe beam to a beam focused to a line in the region, producing an in-focus return probe beam, and producing antisymmetric spatial properties in the in-focus return probe beam (P32B). Then the in-focus return probe beam is spatially filtered (P42A) and passed through a dispersal element to focus it (P42C) to a line in a detector plane of a detector system (114). The reference beam is spatially filtered (R42A) and passed through a dispersal element to focus it (R42C) to a line in-the-detector-plane. A beam from an out-of-focus image point is spatially filtered (P62A) and passed through the dispersal element (P62C). The in-the-detector-plane spatially filtered reference beam (R42C) is interfered with the in-the-detector-plane spatially filtered beam from the out-of-focus image point (P62C) and the in-the-detector-plane spatially filtered in-focus return probe beam (P42C). An amplitude of the spatially filtered in-focus return probe beam (P42C) is detected as an interference term between the in-the-detector-plane spatially filtered reference beam, and the in-the-detector-plane spatially filtered (R42C) in-focus return probe beam (P42C) by means of the detector system (114). An amplitude of an interference term between an amplitude of the in-the-detector-plane spatially filtered out-of-focus image beam (P62C) and an amplitude of the in-the-detector-plane spatially filtered reference beam (R42C) is thereby substantially reduced, and reduces errors in data produced by the detector system (114) to represent the image information of the object.

IPC 1-7
G01B 9/02

IPC 8 full level
G01B 9/02 (2006.01); **G01B 9/04** (2006.01); **G01B 11/00** (2006.01); **G01J 3/51** (2006.01); **G01N 21/17** (2006.01); **G01N 21/27** (2006.01); **G02B 21/00** (2006.01); **G03F 9/00** (2006.01); **G11B 7/005** (2006.01); **G11B 7/0065** (2006.01); **G11B 7/14** (2006.01); **H01L 21/027** (2006.01)

CPC (source: EP)
G01B 9/02027 (2013.01); **G01B 9/02042** (2013.01); **G01B 9/04** (2013.01); **G02B 21/0056** (2013.01); **G02B 21/006** (2013.01); **G02B 21/0068** (2013.01); **G02B 21/008** (2013.01); **G11B 7/005** (2013.01); **G11B 7/14** (2013.01)

Citation (search report)
See references of WO 9963300A1

Designated contracting state (EPC)
CH DE FR GB LI NL SE

DOCDB simple family (publication)
WO 9963300 A1 19991209; CN 1309759 A 20010822; EP 1084378 A1 20010321; JP 2002517710 A 20020618

DOCDB simple family (application)
US 9911601 W 19990526; CN 99808770 A 19990526; EP 99928339 A 19990526; JP 2000552462 A 19990526