

Title (en)

Method for obtaining a heat sensitive element by spray-coating

Title (de)

Verfahren zur Herstellung eines wärmeempfindlichen Elements durch Sprühbeschichtung

Title (fr)

Procédé de fabrication d'un élément thermosensible avec revêtement par pulvérisation

Publication

EP 1084830 B1 20030702 (EN)

Application

EP 99203064 A 19990915

Priority

EP 99203064 A 19990915

Abstract (en)

[origin: EP1084830A1] According to the present invention there is provided a method for obtaining a high quality printing plate by spraying a spray solution on a receiving surface of grained and anodized aluminum, characterized in that the spray factor (SF) is between 48 and 70 mN/m, wherein $SF = (P/d \times \sigma)$ SF: Spray Factor (mN/m) P: Spray Profile (mm) d: distance between spray head and receiving surface (mm) sigma : surface tension (mN/m).

IPC 1-7

B41C 1/10

IPC 8 full level

G03F 7/16 (2006.01); **B05D 3/10** (2006.01); **B05D 7/14** (2006.01); **B41C 1/10** (2006.01); **B41N 1/14** (2006.01); **B41N 3/03** (2006.01); **G03F 7/00** (2006.01)

CPC (source: EP)

B41C 1/1066 (2013.01)

Cited by

EP1839893A1; US6485889B1; CN109396003A; US6479216B1; US7700158B2

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

EP 1084830 A1 20010321; **EP 1084830 B1 20030702**; DE 69909290 D1 20030807; DE 69909290 T2 20040527; JP 2001129960 A 20010515

DOCDB simple family (application)

EP 99203064 A 19990915; DE 69909290 T 19990915; JP 2000269803 A 20000906