

Title (en)

A method for obtaining a heat sensitive element by spray-coating

Title (de)

Verfahren zur Sprühbeschichtung eines wärmeempfindlichen Aufzeichnungselements

Title (fr)

Méthode pour la fabrication d'un élément thermosensible par la pulvérisation du matériau de revêtement

Publication

**EP 1084862 A1 20010321 (EN)**

Application

**EP 99203065 A 19990915**

Priority

EP 99203065 A 19990915

Abstract (en)

According to the present invention there is provided a method for obtaining a high quality printing plate by spraying a spray solution on a receiving surface, which is not a grained and anodized aluminum surface, characterized in that the pressure factor (PF) is lower than 200 mN/m, wherein <MATH> PF: Pressure Factor (mN/m) P: Spray Profile (mm) d: distance between spray head and receiving surface (mm) sigma : surface tension (mN/m).  $\theta$ : Dynamic contact angle of the receiving surface with water at 2 s contact time

IPC 1-7

**B41M 5/36**; **B41C 1/10**

IPC 8 full level

**B05D 1/02** (2006.01); **B05D 7/14** (2006.01); **B05D 7/24** (2006.01); **B41C 1/10** (2006.01); **B41N 1/14** (2006.01)

CPC (source: EP)

**B41C 1/1025** (2013.01); **B41C 1/1066** (2013.01); **B41C 2210/08** (2013.01); **B41C 2210/22** (2013.01); **B41C 2210/24** (2013.01)

Citation (search report)

- [A] US 4626484 A 19861202 - NISHIOKA AKIRA [JP], et al
- [A] EP 0674230 A1 19950927 - AGFA GEVAERT NV [BE]
- [A] EP 0429234 A2 19910529 - DU PONT HOWSON LTD [GB]
- [A] DE 4000405 A1 19910711 - HOECHST AG [DE]

Cited by

EP1642746A1; US6485889B1; US6479216B1; CN101963759A

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

**EP 1084862 A1 20010321**; **EP 1084862 B1 20031112**; DE 69912775 D1 20031218; DE 69912775 T2 20040812; JP 2001121835 A 20010508

DOCDB simple family (application)

**EP 99203065 A 19990915**; DE 69912775 T 19990915; JP 2000269944 A 20000906