

Title (en)

BRANCH-PIPE FERRULE AND METHOD OF INSERTING SAME IN A LINED MAINS-PIPE

Title (de)

ROHRZWEIGZWINGE UND VERFAHREN UM DIESE IN EIN AUSGEKLEIDETES HAUPTRÖHR EINZUFÜHREN

Title (fr)

VIROLE DE TUYAU D'EMBRANCHEMENT ET PROCEDE D'INSERTION DE LADITE VIROLE DANS UNE CANALISATION DU RESEAU DE DISTRIBUTION

Publication

**EP 1086332 A1 20010328 (EN)**

Application

**EP 99937973 A 19990302**

Priority

- GB 9900621 W 19990302
- GB 9804353 A 19980303

Abstract (en)

[origin: WO9945307A1] A ferrule is inserted into an opening (18) formed in a wall of a lined pipe (1, 14) such that a tubular body (4) of the ferrule extends through the opening (18) and the liner (2) is trapped between the pipe (1, 18) and a flange (5) which is supported adjacent one end of the body (4). The ferrule is transported along the interior of the lined pipe from an open end of the pipe to adjacent the opening, the position of the ferrule relative to the opening being assessed visually. A tool is inserted through the opening to engage the ferrule body which is then pulled through the opening from outside the pipe and secured in position such that the flange (5) abuts the liner (2).

IPC 1-7

**F16L 55/16; F16L 41/14**

IPC 8 full level

**F16L 41/14** (2006.01); **F16L 55/179** (2006.01)

CPC (source: EP)

**F16L 41/14** (2013.01); **F16L 55/179** (2013.01)

Citation (search report)

See references of WO 9945307A1

Designated contracting state (EPC)

DE DK ES FR GB IT NL SE

DOCDB simple family (publication)

**WO 9945307 A1 19990910**; AU 3262999 A 19990920; EP 1086332 A1 20010328; GB 9804353 D0 19980422

DOCDB simple family (application)

**GB 9900621 W 19990302**; AU 3262999 A 19990302; EP 99937973 A 19990302; GB 9804353 A 19980303