

Title (en)

REPRODUCING APPARATUS ENABLING THE ACTUAL BEGINNING OF THE REPRODUCTION OF A TELEVISION PROGRAM RECORDED ON A MAGNETIC TAPE

Title (de)

WIEDERGABEEINRICHTUNG, DIE DEN UNMITTELBAREN BEGINN EINER WIEDERGABE EINER AUF EINEM MAGNETBAND AUFGEZEICHNETEN FERNSEHSENDUNG ERMÖGLICHT

Title (fr)

APPAREIL DE REPRODUCTION POUR LANCER LA REPRODUCTION D'UN PROGRAMME TELEVISUEL ENREGISTRE SUR UNE BANDE MAGNETIQUE

Publication

EP 1088307 A1 20010404 (EN)

Application

EP 00931056 A 20000406

Priority

- EP 00931056 A 20000406
- EP 0003071 W 20000406
- EP 99890124 A 19990414

Abstract (en)

[origin: WO0063900A1] In a reproducing apparatus (1) comprising magnetic tape transport means (8) for transporting a magnetic tape (15) with a normal-play reproduction speed (V1), at least one trick-play reproduction speed (V2-V9) and a winding speed (VS, VR), where the at least one trick-play reproduction speed (V2-V9) and the winding speed (VS-VR) are higher than the normal-play reproduction speed (V1), and comprising reproducing means (7, 10) for reproducing digital signal data (SD) from normal-play reproduction areas of a magnetic tape (15) transported by the magnetic tape transport means (8) with the normal-play reproduction speed (V1) or from trick-play reproduction areas from a magnetic tape (15) transported by the magnetic tape transport means (8) with a trick-play reproduction speed (V2-V9), and comprising control means (31) for controlling the magnetic tape transport means (8) in a playback search mode to achieve a transportation of the magnetic tape (15) until a predefined magnetic tape position (P3, P4, P7, P10, P11) is reached with a higher speed than the normal-play reproduction speed (V1) and, subsequently, a transportation of the magnetic tape (15) with the normal-play reproduction speed (V1), assigning means (30) are arranged for assigning at least one predefined magnetic tape position (P3, P4, P7, P10, P11) with an at least one trick-play reproduction speed (V2-V9) and the control means (31) are provided for reaching a predefined magnetic tape position (P3, P4, P7, P10, P11) for controlling the magnetic tape transport means (8) to transport the magnetic tape (15) until the predefined magnetic tape position (P3, P4, P7, P10, P11) is reached with the trick-play reproduction speed (V2-V9) assigned to the predefined magnetic tape position (P3, P4, P7, P10, P11).

IPC 1-7

G11B 15/18; G11B 15/087; G11B 15/467

IPC 8 full level

G11B 15/02 (2006.01); **G11B 15/087** (2006.01); **G11B 15/18** (2006.01); **H04N 5/783** (2006.01); **G11B 15/467** (2006.01); **G11B 20/10** (2006.01); **G11B 20/12** (2006.01); **G11B 27/10** (2006.01); **H04N 5/92** (2006.01); **H04N 5/93** (2006.01)

CPC (source: EP KR)

G11B 5/00813 (2013.01 - KR); **G11B 5/09** (2013.01 - KR); **G11B 15/1875** (2013.01 - EP); **G11B 15/46** (2013.01 - KR); **H04N 5/782** (2013.01 - KR)

Designated contracting state (EPC)

AT DE FR GB

DOCDB simple family (publication)

WO 0063900 A1 20001026; CN 1313986 A 20010919; EP 1088307 A1 20010404; HU P0103326 A2 20011228; HU P0103326 A3 20021228; JP 2002542693 A 20021210; KR 20010052869 A 20010625

DOCDB simple family (application)

EP 0003071 W 20000406; CN 00801054 A 20000406; EP 00931056 A 20000406; HU P0103326 A 20000406; JP 2000612943 A 20000406; KR 20007014207 A 20001214