

Title (en)  
ENVIRONMENTALLY FRIENDLY COMPOSITIONS HAVING ANTI-ICING, DEICING OR GRAFFITI PREVENTION PROPERTIES

Title (de)  
UMWELTFREUNDLICHE ZUSAMMENSETZUNGEN MIT ENTEISUNGS-, VEREISUNGSSCHUTZ- ODER ANTI-GRAFFITI-EIGENSCHAFTEN

Title (fr)  
COMPOSITIONS ECOLOGIQUES ANTIGIVRANTES, DEGIVRANTES ET ANTI-GRAFFITI

Publication  
**EP 1092002 A1 20010418 (EN)**

Application  
**EP 99932030 A 19990629**

Priority  
• US 9914678 W 19990629  
• US 10680398 A 19980629

Abstract (en)  
[origin: WO0000568A1] The present invention describes an aqueous, non-electrolytic, non-toxic, biodegradable, continuous single phase liquid anti-icing or deicing composition for use on the surfaces of, for example, aircraft, airport pavements, roadways, walkways, bridges, entrances, structures, canals, locks, components, vessels, nautical component, railroad switches, and motor vehicles. The anti-icing or deicing composition comprises: (a) water; (b) a non-toxic freezing point depressant selected from the group consisting of monohydric alcohols having from 2 to 6 carbon atoms, polyhydric alcohols having 3 to 12 carbon atoms, monomethyl or ethyl ethers of polyhydric alcohols having from 3 to 12 atoms or mixtures thereof, wherein the freezing point depressant present is between about 14 to 60 percent by weight; (c) a thickener which is present in between about 0.01 and 10 percent by weight; and (d) optionally a corrosion inhibitor which is present in between about 0.01 and 0,1 percent by weight of the total composition. In one embodiment, the deicing composition further includes (e) a monohydric primary aliphatic unbranched alcohol as a means of forming a thin layer on the surface of the composition applied to the structure to be given ice protection, and/or as means of forming a homogenized foam with xanthan thickener; which alcohol is selected from the group consisting of alcohols having between 8 to 24 carbon atoms, preferably, 1-dodecanol. Compositions of water, propylene glycol, and/or propanol and xanthan are preferred. In other embodiments compositions preferably containing a polyol, such as glycerin, are used to produce a coating on an object or surface to protect it from graffiti such as paint, lacquer, ink and the like.

IPC 1-7  
**C09K 3/18**; **C09D 5/00**

IPC 8 full level  
**C09D 5/02** (2006.01); **C09D 5/04** (2006.01); **C09D 105/00** (2006.01); **C09K 3/18** (2006.01)

CPC (source: EP)  
**C09D 5/024** (2013.01); **C09D 5/04** (2013.01); **C09D 105/00** (2013.01); **C09K 3/185** (2013.01)

Citation (search report)  
See references of WO 0000568A1

Cited by  
DE102007012757A1

Designated contracting state (EPC)  
DE FR GB

DOCDB simple family (publication)  
**WO 0000568 A1 20000106**; AU 4842599 A 20000117; CA 2336111 A1 20000106; EP 1092002 A1 20010418

DOCDB simple family (application)  
**US 9914678 W 19990629**; AU 4842599 A 19990629; CA 2336111 A 19990629; EP 99932030 A 19990629