

Title (en)

ARTICULATED OVERHEAD GATE FOR PARTICULARLY SMALL DROP HEIGHTS

Title (de)

DECKENGLIEDERTOR FÜR BESONDERS NIEDRIGE STURZHÖHEN

Title (fr)

PORTE ARTICULEE AU PLAFOND POUR HAUTEURS DE CHUTE PARTICULIÈREMENT FAIBLES

Publication

EP 1092074 B1 20050810 (DE)

Application

EP 98905229 A 19980109

Priority

- DE 9800059 W 19980109
- DE 19700630 A 19970110
- DE 19731932 A 19970724

Abstract (en)

[origin: US6076589A] PCT No. PCT/DE98/00059 Sec. 371 Date Sep. 28, 1998 Sec. 102(e) Date Sep. 28, 1998 PCT Filed Jan. 9, 1998 PCT Pub. No. WO98/30776 PCT Pub. Date Jul. 16, 1998An articulated overhead gate for gate openings with particularly small drop heights between the upper edge of the gate opening that is to be closed and an adjoining overhead area or similar with a gate leaf consisting of several panels (3, 5) articulated successively in the direction of movement, which are driven by laterally arranged rollers (2) in first lateral roller rails (6), connected in an approximately vertical and thereby curved horizontal direction, excepting the upper panel (5) in closed position, which engages with its rollers (4) which, in this position, are arranged in the upper edge area (30), in second roller rails (7). Said roller rails are parallel to and located above the facing horizontal segments of the first roller rails (6), each segment having an end part (8) facing the gate frame, a first section (10) of which part is lowered only slightly in relation to the horizontal, and a second section (11) correspondingly inclining only slightly over 90 DEG to the horizontal in the direction of the ground. The articulated overhead gate is optionally designed, for manual gate-leaf or motor-driver actuation so that the rollers (4) of the upper panels (5) can be optionally arranged in order to be vertically displaceable in relation to their axes, and so that the transition areas (19) between the first and second sections (10, 11) are each optionally provided with a spring element (12, 15, 15') with a non-rigid deflection surface for the suspension of the roller (4) entering the transition region (19), and for the deflection of the same from one section into the other.

IPC 1-7

E05D 15/24

IPC 8 full level

E05D 15/24 (2006.01); **E05F 15/00** (2015.01)

CPC (source: EP US)

E05D 15/24 (2013.01 - EP US); **E05D 15/246** (2013.01 - EP US); **E05F 15/668** (2015.01 - EP US); **E05Y 2600/40** (2013.01 - EP US);
E05Y 2900/106 (2013.01 - EP US); **Y10S 292/36** (2013.01 - EP US); **Y10T 292/0882** (2015.04 - EP US)

Designated contracting state (EPC)

AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

US 6076589 A 20000620; AT E301760 T1 20050815; CN 1105223 C 20030409; CN 1216084 A 19990505; CZ 288298 A3 19990317;
CZ 295178 B6 20050615; EP 1092074 A1 20010418; EP 1092074 B1 20050810; ES 2245023 T3 20051216; HU 221555 B 20021128;
HU P9903057 A2 20000228; HU P9903057 A3 20000628; NO 310522 B1 20010716; NO 984039 D0 19980903; NO 984039 L 19980910;
PL 186477 B1 20040130; PL 328813 A1 19990215; WO 9830776 A1 19980716

DOCDB simple family (application)

US 14280398 A 19980928; AT 98905229 T 19980109; CN 98800023 A 19980109; CZ 288298 A 19980109; DE 9800059 W 19980109;
EP 98905229 A 19980109; ES 98905229 T 19980109; HU P9903057 A 19980109; NO 984039 A 19980903; PL 32881398 A 19980109