

Title (en)
LOCKING DEVICE

Title (de)
VERRIEGELUNGSVORRICHTUNG

Title (fr)
DISPOSITIF DE VERROUILLAGE

Publication
EP 1095199 A1 20010502 (EN)

Application
EP 99935238 A 19990706

Priority
• SE 9901227 W 19990706
• SE 9802416 A 19980706

Abstract (en)
[origin: WO0001909A1] The present invention relates to a device for guiding and locking a casement in a window-frame, the device comprising pistons (10, 11, 10', 11') which are extendable from and retractable into the casement and arranged in corner portions of the casement in order to engage in a locked position one groove each of the frame. When the window is locked, the pistons (10, 11, 10', 11') are in a partly extended position for engaging the frame, and the pistons (10', 11') located on a first casement side are connected to a first link construction (2'), while the pistons (10, 11) located on the opposite casement side are connected to a second link construction (2). The two link constructions (2, 2') are arranged adjacent to a turning member (15) for simultaneous motion of the link constructions (2, 2') in opposite directions of motion, said motion causing one pair of opposite pistons (10, 10') to be moved from a partly extended to a completely retracted position, while the other pair of opposite pistons (11, 11') is moved from a partly extended to a completely extended position, or vice versa, for opening and closing the window.

IPC 1-7
E05D 15/44

IPC 8 full level
E05C 9/06 (2006.01)

CPC (source: EP)
E05C 9/063 (2013.01); **E05C 9/14** (2013.01); **E05D 15/502** (2013.01); **E05Y 2900/148** (2013.01)

Citation (search report)
See references of WO 0001909A1

Designated contracting state (EPC)
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
WO 0001909 A1 20000113; AU 5075799 A 20000124; EP 1095199 A1 20010502; SE 512368 C2 20000306; SE 9802416 D0 19980706; SE 9802416 L 20000107

DOCDB simple family (application)
SE 9901227 W 19990706; AU 5075799 A 19990706; EP 99935238 A 19990706; SE 9802416 A 19980706