

Title (en)

A method for making a flexible conductor and a flexible conductor

Title (de)

Methode zur Herstellung eines flexiblen Leiters und ein flexibler Leiter

Title (fr)

Méthode pour la fabrication d'un conducteur flexible et un conducteur flexible

Publication

EP 1098326 A3 20020123 (EN)

Application

EP 00122500 A 20001014

Priority

DK PA199901589 A 19991104

Abstract (en)

[origin: EP1098326A2] There is described a method for making a flexible conductor (15) with connecting terminals (21) at both ends and consisting of one or more flexible, braided copper bands (4, 6), by which method a copper band, preferably from a coil, is supplied to a two-part forging tool (16) in a press, e.g. an eccentric press, that protective gas (nitrogen) is supplied to the forging tool for protecting the structure of the copper and for displacing oxygen and avoiding discolouring of the copper band, that the copper band (4, 6) is subjected to a very great current intensity between points at each side of the forging tool so that the part of the copper band situated in the forging tool (16) is heated to red-hot condition, that the current is switched off and that the press is simultaneously activated for bringing together the tool parts for compressing and forging the said part of the copper band so that it subsequently appears as a solid and homogenous piece of copper of which the connecting terminals are formed, either by an immediately succeeding operation or by a later operation. Hereby it is achieved that by means of simple technical measures it becomes possible to make a new and improved flexible conductor making possible to reduce the number of conductors stocked very significantly as the conductor according to the invention, according to need, may consist of several parallel, preferably identical, copper bands with integrated end terminals of solid and/or homogenous copper. <IMAGE>

IPC 1-7

H01B 5/12

IPC 8 full level

H01B 5/12 (2006.01)

CPC (source: EP)

H01B 5/12 (2013.01)

Citation (search report)

- [A] US 1731218 A 19291008 - ADAMS NATHAN H
- [A] GB 1209258 A 19701021 - HEAD BRAIDING LTD, et al

Cited by

CN111725679A; GB2452674B; CN102449858A; CN102856675A; CN112530638A

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

EP 1098326 A2 20010509; EP 1098326 A3 20020123; EP 1098326 B1 20060118; AT E316286 T1 20060215; DE 60025564 D1 20060406; DE 60025564 T2 20060921; DK 1098326 T3 20060515

DOCDB simple family (application)

EP 00122500 A 20001014; AT 00122500 T 20001014; DE 60025564 T 20001014; DK 00122500 T 20001014