

Title (en)
Torque converter

Title (de)
Momentwandler

Title (fr)
Convertisseur de couple

Publication
EP 1099879 B1 20050817 (EN)

Application
EP 00124227 A 20001109

Priority
JP 31913799 A 19991110

Abstract (en)
[origin: EP1099879A2] A torque converter is formed such that a flatness ($2L/H$) and a torus inside and outside radius ratio (r/R) satisfy equations; (1) $0.55 < (2L/H) < 0.75$ and (2) $35 < (r/R) < 0.40$. Then, assuming that an axially central position of the flow path along a rotational shaft of the torque converter is an origin, an axial direction is an X direction and a radial direction is a Y direction, the configuration of the flow path of the turbine member is set such that the position of a point of contact between a straight line inclined 45 degrees relative to the X direction and a curve constituting an external circumferential surface of the flow path in the turbine member is located within an area surrounded by two straight lines expressed as (3) $Y = (R/L) \times X + (6/4) \times R$ and (4) $Y = (R/L) \times X + (7/4) \times R$. <IMAGE>

IPC 1-7
F16H 41/24; **F16H 41/26**

IPC 8 full level
F16H 41/26 (2006.01)

CPC (source: EP US)
F16H 41/26 (2013.01 - EP US); **F16H 2045/0294** (2013.01 - EP US)

Cited by
EP2065618A1; EP1298352A3; WO2004042255A1; EP1298352A2; US6807808B2

Designated contracting state (EPC)
DE GB

DOCDB simple family (publication)
EP 1099879 A2 20010516; **EP 1099879 A3 20040512**; **EP 1099879 B1 20050817**; CA 2323408 A1 20010510; CA 2323408 C 20040106; DE 60021984 D1 20050922; DE 60021984 T2 20060323; JP 2001141026 A 20010525; US 6447246 B1 20020910

DOCDB simple family (application)
EP 00124227 A 20001109; CA 2323408 A 20001017; DE 60021984 T 20001109; JP 31913799 A 19991110; US 70783800 A 20001108