

Title (en)

Procedure for the removal of punctiform raised lacquer

Title (de)

Verfahren zur Beseitigung punktförmiger Lackerhebungen

Title (fr)

Procédure d'élimination de défauts de laque en forme de point

Publication

**EP 1101539 B1 20070502 (DE)**

Application

**EP 00124262 A 20001113**

Priority

DE 19955012 A 19991116

Abstract (en)

[origin: EP1101539A2] In the method the esp. clear varnish region surrounding the varnish concn., (20), is covered before the grinding off operation, by a protective foil (10) with an opening (12) leaving exposed solely the clear varnish concn. (20) and its direct surrounding. The dia. of the opening (12) for the individual varnish lumps is selected respectively matching depending on the foil thickness and the foil material.

IPC 8 full level

**B05D 1/32** (2006.01); **B05D 3/12** (2006.01); **B05D 5/00** (2006.01); **B05D 7/14** (2006.01)

CPC (source: EP)

**B05D 3/12** (2013.01); **B05D 5/005** (2013.01)

Cited by

WO0168270A3

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR

DOCDB simple family (publication)

**EP 1101539 A2 20010523**; **EP 1101539 A3 20010704**; **EP 1101539 B1 20070502**; AT E361155 T1 20070515; DE 19955012 A1 20010517; DE 50014293 D1 20070614

DOCDB simple family (application)

**EP 00124262 A 20001113**; AT 00124262 T 20001113; DE 19955012 A 19991116; DE 50014293 T 20001113