

Title (en)

A terminal tool for prop with variable inclination

Title (de)

Endstück für eine Stütze mit verstellbarer Neigung

Title (fr)

Outil terminal pour étau à inclinaison variable

Publication

EP 1106749 A1 20010613 (EN)

Application

EP 00830644 A 20000929

Priority

IT RE990055 U 19991130

Abstract (en)

A prop (1) for shoring structures, in particular forms for concrete castings, particularly useful in the case of structures having an inclined surface relative to the ground. The prop comprises a rod (2) with adjustable length and it is provided with a head (8) pivotally engaged to the rod, through a rotating element (12). The placement of the prop (1) takes place by setting the prop in the vertical position relative to the ground, adapting the head (8) to the inclined surface of the structure to be supported and locking such configuration of the head (8) with appropriate fastening means (13), operating on the rotating element (12). <IMAGE>

IPC 1-7

E04G 25/00; **E04G 25/06**

IPC 8 full level

E04G 25/00 (2006.01); **E04G 25/06** (2006.01)

CPC (source: EP)

E04G 25/00 (2013.01); **E04G 25/06** (2013.01); **E04G 25/061** (2013.01); **E04G 25/065** (2013.01); **E04G 2025/006** (2013.01)

Citation (search report)

- [XA] CH 259761 A 19490215 - DAELLENBACH WERNER [CH]
- [X] GB 1124201 A 19680821 - SUPERIOR SCAFFOLD COMPANY
- [XA] DE 29606287 U1 19960620 - HERZBERGER GERHARD [DE]
- [X] CH 523406 A 19720531 - MEYER EMIL [CH]
- [A] US 5934631 A 19990810 - BECKER JESSICA R [US], et al
- [XA] PATENT ABSTRACTS OF JAPAN vol. 1999, no. 05 31 May 1999 (1999-05-31)
- [X] PATENT ABSTRACTS OF JAPAN vol. 1996, no. 09 30 September 1996 (1996-09-30)

Cited by

CN111576925A; CN112031465A; CN111910953A; ES2261103A1; CN111927093A; FR3115804A1

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

EP 1106749 A1 20010613; IT 248288 Y1 20021216; IT RE990055 U1 20010530

DOCDB simple family (application)

EP 00830644 A 20000929; IT RE990055 U 19991130